

T495B226K006ZTE500

Obsolete

B450, Tantalum, MnO₂ Tantalum, 22 uF, 10%, 6.3 VDC, SMD, Molded, Low ESR, Surge Robust, 500 mOhms, 3528, Height Max = 2.1mm



General Information

| | |
|-------------|---|
| Series | B450 |
| Dielectric | MnO ₂ Tantalum |
| Style | SMD Chip |
| Description | SMD, Molded, Low ESR, Surge Robust |
| Features | Low ESR, Surge Robust |
| RoHS | Yes |
| Termination | Tin |
| AEC-Q200 | No |
| Notes | Obsolete. Old part number [Obsolete] was B45006B2269K507. |

Specifications

| | |
|-----------------------|--|
| Capacitance | 22 uF |
| Capacitance Tolerance | 10% |
| Voltage DC | 6.3 VDC (85C), 4.22 VDC (125C) |
| Temperature Range | -55/+125°C |
| Rated Temperature | 85°C |
| Dissipation Factor | 6% |
| Failure Rate | N/A |
| Resistance | 0.5 Ohms (100kHz) |
| Ripple Current | 410 mAmps (25C), 369 mAmps (85C), 164 mAmps (125C) |
| Leakage Current | 1.4 uA |

Dimensions

| | |
|-----------|----------------|
| Footprint | 3528 |
| L | 3.5mm +/-0.2mm |
| W | 2.8mm +/-0.2mm |
| H | 1.9mm +/-0.2mm |
| S | 0.7mm +/-0.3mm |
| F | 2.2mm +/-0.1mm |
| K | 1.4mm TYP |

Packaging Specifications

| | |
|--------------------|------------|
| Packaging | T&R, 178mm |
| Packaging Quantity | 2000 |