

GP1L53V

Compact, High Sensing Accuracy Type Photointerrupter

■ Features


1. Compact type
2. High sensing accuracy (Slit width: 0.5mm)
3. High current transfer ratio
(CTR: MIN. 30% at $I_F = 1\text{mA}$)
4. PWB direct mounting type

■ Applications

1. OA equipment such as FDDs, printers, facsimiles, etc.
2. VCRs
3. Optoelectronic switches

■ Outline Dimensions

(Unit : mm)



■ Absolute Maximum Ratings

(Ta = 25°C)

Parameter		Symbol	Rating	Unit
Input	Forward current	I_F	50	mA
	*1 Peak forward current	I_{FM}	1	A
	Reverse voltage	V_R	6	V
	Power dissipation	P	75	mW
Output	Collector-emitter voltage	V_{CEO}	35	V
	Emitter-collector voltage	V_{ECO}	6	V
	Collector current	I_C	40	mA
	Collector power dissipation	P_C	75	mW
Operating temperature		T_{opr}	- 25 to + 85	°C
Storage temperature		T_{stg}	- 40 to + 100	°C
*2 Soldering temperature		T_{sol}	260	°C

*1 Pulse width ≤ 100μs, Duty ratio = 0.01

*2 For 5 seconds

■ Electro-optical Characteristics

(Ta = 25°C)

Parameter			Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Input	Forward voltage		V _F	I _F = 20mA	-	1.25	1.4	V
	Peak forward voltage		V _{FM}	I _{FM} = 0.5A	-	3	4	V
	Reverse current		I _R	V _R = 3V	-	-	10	μ A
Output	Collector dark current		I _{CEO}	V _{CE} = 10V	-	-	10 ^{- 6}	A
Transfer charac- teristics	Collector Current		I _C	I _F = 1mA, V _{CE} = 2V	0.3	-	20	mA
	Collector-emitter saturation voltage		V _{CE(sat)}	I _F = 2mA, I _C = 0.3mA	-	-	1.0	V
	Response time	Rise time	t _r	V _{CE} = 2V, I _C = 2mA	-	80	400	μ s
		Fall time	t _f	R _L = 100 Ω	-	70	350	μ s

Fig. 1 Forward Current vs. Ambient Temperature




Fig. 2 Collector Power Dissipation vs. Ambient Temperature




Fig. 3 Peak Forward Current vs. Duty Ratio




Fig. 4 Forward Current vs. Forward Voltage




Fig. 5 Collector Current vs. Forward Current




Fig. 6 Collector Current vs. Collector-emitter Voltage




Fig. 7 Collector Current vs. Ambient Temperature




Fig. 8 Collector-emitter Saturation Voltage vs. Ambient Temperature





Fig. 9 Response Time vs. Load Resistance



Test Circuit for Response Time




Fig.10 Frequency Response




Fig.11 Collector Dark Current vs. Ambient Temperature




Fig.12 Relative Collector Current vs. Shield Distance (1)





Fig.13 Relative Collector Current vs. Shield Distance (2)



■ Precautions for Use

- (1) In case of cleaning, use only the following type of cleaning solvent.
Ethyl alcohol, Methyl alcohol, Isopropyl alcohol
- (2) As for other general cautions, refer to the chapter "Precautions for Use".