


## 4,000 V BREAKDOWN VOLTAGE DS RELAYS

# DS-BT RELAYS



mm inch

## FEATURES

- 4,000 V breakdown voltage
- Reinforced insulation between coil and contacts
- Surge voltage withstand: 1500 V FCC Parts 68

## SPECIFICATIONS

### Contact

Arrangement	2 Form C	2 Form D
Initial contact resistance, max. (By voltage drop 6 V DC 1 A)	50 mΩ	
Contact material	Gold-clad silver	
Rating (resistive load)	Nominal switching capacity	2 A 30 V DC    1 A 30 V DC
	Max. switching power	60 W, 125 VA    30 W, 62.5 VA
	Max. switching voltage	220 V DC, 250 V AC
	Max. switching current	2 A    1 A
Electrical life (min. ope.)	Min. switching capacity**1	10 μA 10 mV DC
	Mechanical (at 180 cpm)	2×10 <sup>7</sup> 10 <sup>6</sup>
	Electrical (at 20 cpm)	2×10 <sup>5</sup>

\*\*1 This value can change due to the switching frequency, environmental conditions, and desired reliability level, therefore it is recommended to check this with the actual load.

### Coil

Arrangement	2 Form C	2 Form D
Nominal operating power	360 mW	540 mW

### Remarks

- \* Specifications will vary with foreign standards certification ratings.
- \*1 Measurement at same location as "Initial breakdown voltage" section
- \*2 Detection current: 10mA
- \*3 Excluding contact bounce time
- \*4 Half-wave pulse of sine wave: 11ms, detection time: 10μs
- \*5 Half-wave pulse of sine wave: 6ms
- \*6 Detection time: 10μs
- \*7 Refer to 5. Conditions for operation, transport and storage mentioned in AMBIENT ENVIRONMENT in catalog

### Characteristics

Arrangement	2 Form C	2 Form D	
Max. operating speed	60 cpm at rated load		
Initial insulation resistance*1	Min. 100 MΩ (at 500 V DC)		
Initial break-down voltage*2	Between open contacts	750 Vrms for 1 min.    500 Vrms for 1 min.	
	Between contacts and coil	4,000 Vrms for 1 min.	
	Between contacts sets	750 V    500 V	
FCC surge voltage between open contacts	1,500 V		
Operate time*3 (at nominal voltage)	Approx. 3 ms		
Release time (without diode)*3 (at nominal voltage)	Approx. 2 ms		
Temperature rise	Max. 65°C		
Vibration resistance	Functional*4	10 to 55 Hz at double amplitude of 3.3 mm	
	Destruction*5	10 to 55 Hz at double amplitude of 5 mm	
Shock resistance	Functional*6	Min. 294 m/s <sup>2</sup> (30 G)	
	Destruction	Min. 980 m/s <sup>2</sup> (100 G)	
Conditions for operation, transport and storage*7 (Not freezing and condensing at low temperature)	Ambient temp.	-40°C to +70°C    -40°F to +158°F	
	Humidity	5 to 85%R.H.	
Unit weight	Approx. 4.0 g 0.14 oz		

## TYPICAL APPLICATIONS    ORDERING INFORMATION

Modem  
Facsimile  
Telecommunication equipment

# DS-BT

## TYPES AND COIL DATA (at 20°C 68°F)

### 1) 2 Form C type


Operating function	Part No.	Coil voltage, V DC	Pick-up voltage, V DC (max.)	Drop-out voltage, V DC (min.)	Nominal operating current, mA (±10%)	Coil resistance, Ω (±10%)	Nominal operating power, mW	Max. allowable voltage, V DC (at 50°C 122°F)
Single side stable	DSBT2-S-DC1.5V	1.5	1.125	0.15	240	6.25	360	1.95
	DSBT2-S-DC3V	3	2.25	0.3	120	25		3.9
	DSBT2-S-DC5V	5	3.75	0.5	72	69.4		6.5
	DSBT2-S-DC6V	6	4.5	0.6	60	100		7.8
	DSBT2-S-DC9V	9	6.75	0.9	40	225		11.7
	DSBT2-S-DC12V	12	9	1.2	30	400		15.6
	DSBT2-S-DC24V	24	18	2.4	15	1,600		31.2

### 2) 2 Form D type

Operating function	Part No.	Coil voltage, V DC	Pick-up voltage, V DC (max.)	Drop-out voltage, V DC (min.)	Nominal operating current, mA (±10%)	Coil resistance, Ω (±10%)	Nominal operating power, mW	Max. allowable voltage, V DC (at 50°C 122°F)
Single side stable	DSBT2-M-2D-DC1.5V	1.5	1.125	0.15	360	4.2	540	1.8
	DSBT2-M-2D-DC3V	3	2.25	0.3	180	16.7		3.6
	DSBT2-M-2D-DC5V	5	3.75	0.5	108	46.3		6
	DSBT2-M-2D-DC6V	6	4.5	0.6	90	66.7		7.2
	DSBT2-M-2D-DC9V	9	6.75	0.9	60	150		10.8
	DSBT2-M-2D-DC12V	12	9	1.2	45	266.7		14.4
	DSBT2-M-2D-DC24V	24	18	2.4	22.5	1,066.7		28.8

Note: Standard packing Tube: 25 pcs. Case: 1,000 pcs.


## DIMENSIONS



General tolerance:  $\pm 0.3 \pm .012$


mm inch

PC board pattern (Bottom view)



Tolerance:  $\pm 0.1 \pm .004$

Schematic (Bottom view)



## REFERENCE DATA


### 1. Mechanical life test

Tested sample: DSBT2-S-DC5V, 10 pcs.


Coil applied voltage: 5 V DC

Operating frequency: 30 cpm

### Change of pick-up and drop-out voltage





### Change of contact resistance




2. Electrical life test (resistive)

Tested sample: DSBT2-S-DC12V, 6 pcs.  
 Condition: 2 A 30 V DC resistive load, 30 cpm  
 Circuit




3. Coil temperature rise

Tested sample: DSBT2-S-DC12V, 5 pcs.  
 Measured portion: Inside the coil




4. Operate and release time characteristics


Tested sample: DSBT2-S-DC5V, 10 pcs.  
 Ambient temperature: 23°C 73°F




Without diode (T1)




Without diode (T2)



Without diode (T3)




Without diode (T4)




5. Distribution of pick-up and drop-out voltage

Tested sample: DSBT2-S-DC5V, 50 pcs.  
 Pick-up voltage




Drop-out voltage



6. Distribution of breakdown voltage

(between contacts and coil)  
 Tested sample: DSBT2-S-DC5V, 100 pcs.



For Cautions for Use, see Relay Technical Information in catalog.