

SLCAB AND SLMCAB SELF-REGULATING HEATING CABLE

Self-Regulating heating cable automatically adjusts heat output based upon surface temperature and ambient conditions. Ideal for freeze protection and low-temperature process maintenance applications.



- Up to 15 W/ft (49 W/m)
- Safe to overlap and insulate
- No temperature controller required
- Safe for use in harsh chemical environments
- Can be cut to length and terminated in the field



Available wattages:

SLCAB: 3, 5, 8, 10 W/ft (10, 16, 26, 33 W/m)

SLMCAB: 5, 10, 15 W/ft (16, 33, 49 W/m)



APPROVED FOR USE IN HAZARDOUS-AREA LOCATIONS



Ordinary Locations

Hazardous Locations

Class I, Division 1 and 2, Groups B, C, D
Class II, Division 2, Groups F, G
Class III, Division 1 and 2



Ordinary Locations

130-03 (-G, -W, -S)

Hazardous Locations

Class I, Division 1 and 2, Groups A, B, C, D
Class II, Division 1 and 2, Groups E, F, G
Class III, Division 1 and 2



Hazardous Locations

II 2 GD

Ex e IIC T* Gb

Ex tb IIIC T*°C Db



Hazardous Locations

Ex e IIC T* Gb

Ex tb IIIC T*°C Db



MADE
IN THE **USA** 

