

# ME B-SA/NS 35 GY - Cover



2202420

<https://www.phoenixcontact.com/pc/products/2202420>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Terminal cover, 1 strip covers up to 12 terminal points, for ME-BUS male side, (female side)



## Your advantages

- Easy, tool-free mounting
- Flammability rating V0 in accordance with UL 94

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 2202420                        |
| Packing unit                         | 10 pc                          |
| Minimum order quantity               | 10 pc                          |
| Note                                 | Made to order (non-returnable) |
| Product key                          | ACHACZ                         |
| GTIN                                 | 4055626113739                  |
| Weight per piece (including packing) | 5.15 g                         |
| Weight per piece (excluding packing) | 4.55 g                         |
| Customs tariff number                | 39269097                       |
| Country of origin                    | DE                             |

2202420

<https://www.phoenixcontact.com/pc/products/2202420>

## Technical data

### Product properties

|                              |   |
|------------------------------|---|
| Product type                 | Filler plug                             |
| Type                         | For ME-BUS connector side (female side) |
| Housing type                 | DIN rail housing                        |
| Ventilation openings present | no                                      |
| Housing series               | ME                                      |

### Dimensions

|                                 |         |
|---------------------------------|---------|
| Width                           | 14.5 mm |
| Height                          | 91.1 mm |
| Depth                           | 17.9 mm |
| Depth from top edge of DIN rail | 15.2 mm |

### Material specifications

|  |             |
|--|-------------|
| Color                                  | gray (7042) |
| Flammability rating according to UL 94 | V0          |
| CTI according to IEC 60112             | 600         |
| Surface characteristics                | untreated   |
| Housing material                       | Polyamide   |

### Environmental and real-life conditions

#### Ambient conditions

|   |  |
|---|--|
| Max. IP code to attain                  | IP20   |
| Ambient temperature (operation)         | -40 °C ... 105 °C (depending on power dissipation) |
| Ambient temperature (storage/transport) | -40 °C ... 55 °C                                   |
| Ambient temperature (assembly)          | -5 °C ... 100 °C                                   |
| Relative humidity (storage/transport)   | 80 %   |

### Mounting

|               |         |
|---------------|---------|
| Mounting type | Snap in |
|---------------|---------|

# ME B-SA/NS 35 GY - Cover

2202420

<https://www.phoenixcontact.com/pc/products/2202420>



## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27182702 |
| ECLASS-13.0 | 27190605 |

### ETIM

|          |          |
|----------|----------|
| ETIM 8.0 | EC001031 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 31261500 |
|-------------|----------|

# ME B-SA/NS 35 GY - Cover

2202420

<https://www.phoenixcontact.com/pc/products/2202420>



## Environmental product compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)