

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		USB2.0 SPECIFICATION AND MICRO-USB CABLES AND CONNECTORS SPECIFICATION		△		
RATING	OPERATING TEMPERATURE RANGE	-30 °C TO +85° C	△	STORAGE TEMPERATURE RANGE	-30 °C TO +85 °C	△
	VOLTAGE	-		OPERATING HUMIDITY RANGE	- % TO - %	
	CURRENT	-		APPLICABLE CABLE	-	
SPECIFICATIONS						
ITEM	TEST METHOD	REQUIREMENTS		QT	AT	
CONSTRUCTION						
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.			
MARKING	CONFIRMED VISUALLY.			X	X	X
REVISIONS						
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE		
△ 3	DIS-E-001673	TS. SAKAI ZAWA	KN. ICHIKAWA	07.07.24		
REMARK						
	APPROVED	A0. SUZUKI	07.03.06			
	CHECKED	HK. TAMAKA	07.03.06			
	DESIGNED	TS. SAKAI ZAWA	07.03.06			
	DRAWN	TS. SAKAI ZAWA	07.03.06			
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-126148-00			
HRS		SPECIFICATION SHEET		ZX20-B-SLDC		
		HIROSE ELECTRIC CO., LTD.		CODE NO.	CL242-0022-1-00	