

Product: <u>5320UE</u> ☑ Security & Sound, 2 Conductor 18 AWG BC, Riser

Product Description

Security & Sound Cable, 2 Conductor 18 AWG solid bare copper conductors with polyolefin insulation, Riser, PVC jacket with ripcord.

Technical Specifications

Product Overview

	cations:	Address	sable Fire Sy	vstems, Data Circu	its, Monitor/I	Detection, C	Control C	ircuits, I	nitiating	Circuits, N	Notification C	Circuits
Constructi	on Details											
Conductor												
Element	No. of Elements	Size	Stranding	Material								
Conductor(s)	2	18 AWG	Solid	BC - Bare Coppe								
nsulation												
Element	Material	Nom. 1	Thickness	Nom. Insulation	Diameter (Color Code						
Conductor(s)	PP - Polypropyler	ie 0.007 in	n (0.18 mm)	0.055 in (1.4 mm)	E	Black, Red						
Outer Shield												
Material												
No Shield												
Outer Jacket												
Materi	ial Nom.	Thickness	s Nom. Dia	ameter Ripcord								
PVC - Polyving	yl Chloride 0.017	in (0.43 mm										
		111 (0.43 1111	n) 0.143 in	Yes								
Overall Cable	Diameter (Nomina		,	Yes								
Electrical C		I): 0.143 in	,	Yes								
Electrical C	Diameter (Nomina	I): 0.143 in	1		Currant							
Electrical C Electricals Nom. Conduc	Diameter (Nomina Characteristic	I): 0.143 in	,		. Current Conductor a	at 25°C						
Electrical C Electricals Nom. Conduc 6.4 Ohm/1000	Diameter (Nomina Characteristic	I): 0.143 in S	1	Cond Ma:		at 25°C						
Electrical C Electricals Nom. Conduc	Diameter (Nomina Characteristic tor DCR Nom. C ft 23 pF/ft	I): 0.143 in S	1	Cond Ma:		at 25°C						
Electrical C Electricals Nom. Conduc 6.4 Ohm/1000 /oltage	Diameter (Nomina Characteristic tor DCR Nom. C ft 23 pF/ft	I): 0.143 in S	1	Cond Ma:		at 25°C						
Electrical C Electricals Nom. Conduct 6.4 Ohm/1000 Voltage UL Voltage R 300 V	Diameter (Nomina Characteristic etor DCR Nom. C ft 23 pF/ft ating	: 0.143 in :S :apacitanc: . (75 pF/m)	1	Cond Ma:		at 25°C						
Electrical C Electricals Nom. Conduct 6.4 Ohm/1000 Voltage UL Voltage R 300 V	Diameter (Nomina Characteristic tor DCR Nom. C ft 23 pF/ft	: 0.143 in :S :apacitanc: . (75 pF/m)	1	Cond Ma:		at 25°C						
Electrical C Electricals Nom. Conduc 6.4 Ohm/1000 /oltage UL Voltage R 300 V Mechanica	Diameter (Nomina Characteristic etor DCR Nom. C ft 23 pF/ft ating	: 0.143 in :S :apacitanc: . (75 pF/m)	1	Cond Ma:		t 25°C						
Electrical C Electricals Nom. Conduc 6.4 Ohm/1000 Voltage UL Voltage R 300 V Mechanica Temperature UL Temperatu	Diameter (Nomina Characteristic stor DCR Nom. C ft 23 pF/fi ating	: 0.143 in :s :apacitance : (75 pF/m) tics	1	Cond Ma:		at 25°C						
Electrical C Electricals Nom. Conduc 6.4 Ohm/1000 Voltage UL Voltage R 300 V Mechanica Temperature UL Temperature	Diameter (Nomina Characteristic tor DCR Nom. C ft 23 pF/ft ating I Characteris ure Operating	: 0.143 in :s :apacitance : (75 pF/m) tics	1	Cond Ma:		t 25°C						
Electrical C Electricals Nom. Conduc 6.4 Ohm/1000 /oltage UL Voltage R 300 V	Diameter (Nomina Characteristic ctor DCR Nom. C ft 23 pF/ft ating I Characteris ure Operating 0°C To +75°C	apacitance (75 pF/m)	1	Cond Ma:		t 25°C						
Electrical C Electricals Nom. Conduc 6.4 Ohm/1000 Voltage UL Voltage R 300 V Vechanica Vechanica UL Temperature UL Temperature Son C Send Radius	Diameter (Nomina Characteristic ctor DCR Nom. C ft 23 pF/ft ating I Characteris ure Operating 0°C To +75°C in. Installation I	apacitance (75 pF/m)	1	Cond Ma:		t 25°C						

Bulk Cable Weight:

15 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor - Riser, Indoor
Flammability / Reaction to Fire:	UL1666 Riser, FT4, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMR
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	6320UE

History

Update and Revision: Revision Number: 0.381 Revision Date: 12-20-2022

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC
5320UE 008U1000	Gray	UnReel	1,000 ft	612825421580
5320UE 008Z1000	Gray	ReelTuff Box	1,000 ft	612825160588

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.