

Que-2-TXT™ Questions? scan to text us fast



F36 PLASTIC LED SIGN RETROFIT LAMP

DOUBLE SIDE LIT, HIGH BRIGHTNESS



specifications

| Vo | ltage | CRI | BASE | Lens | Heat Sink | L70 hours | Ambient Temp (F) | Power Factor | IP Rating | THC: | Beam Angle |
|--------------|---------|-----|--------|-----------------------|-----------|-----------|---------------------|--------------|--------------------------|------|------------|
| 9 100 |)-277 V | 83 | R17D d | ouble-side plastic | aluminum | 50,000 | -22°- 131° | >0.9 e | IP 64 except for base | <15% | 360° |

select your lamp

| Part Number | Color Temp | Consumption | Lumen Output | Efficacy | Length (pin to pin) | Diameter |
|----------------------|------------|-------------|-----------------|------------|------------------------|----------|
| GI-F36T10-CC45-R17D4 | 6000K | 16W | 1,920 | 120 lm / w | 33.91 | 1.28" |

| Warranty | Weight | Case QTY | |
|----------|----------|----------|--|
| 6 years | 1.23 lbs | 10 pcs | |

Features

- Rotatable base
- Rated for fully enclosed fixtures
 - 50,000 hour LED lifespan based on IES LM-80 results and TM-21 calculations
- Double-side powered
- Designed for double sided signs
- Replaces F36T12/HO lamps















