


HC-B 16-TFL-76/O1STM32S

Order No.: 1645053



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1645053>

HEAVYCON sleeve housing B16, for single locking latch, height 76 mm, without support 1x M32, lateral conductor exit

Commercial data	
GTIN (EAN)	 4 017918 912918
sales group	D002
Pack	10 pcs.
Customs tariff	85389099
Catalog page information	Page 488 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
02/28/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.


Technical data

General data	
Note	For contact inserts HC-B16, BB32, D40, DD72, HS6, M, K
Design	B16
Height	76 mm
Width	43 mm

Length	94 mm
Housing type	Sleeve housings
Locking type	for single locking latch
Cable exit	Lateral
Type of the screw connection	1x M32
Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 125 °C
Housing material	Aluminum, die-cast
Housing surface material	Powder-coated, gray

Diagrams/Drawings

Dimensioned drawing



Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;