60 INCHES LENGTH



Connector A 132245 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 262121 MMCX Jack Straight Bulkhead - Rear Mount Brass Gold + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Right Angle		Connector /	Cable			Connector B		
135" 180° 225° 270° 315° 270° D-Flat Bulkhead	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting:	132245	K RG174 RG316 LMR100 Mount	Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 60 Inches	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Material: Body Finish: IP Rating: Contact Material: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	262121	
Amphenol CUSTOM CABLE CONTROLLED DOCUMENT DO NOT CORV PROPRIETARY FOR ANY PURP INC. IT MAY NO CUSTOM CABLE			PROPRIETARY INFORMATION A FOR ANY PURPOSE DETRIMENT INC. IT MAY NOT BE REPRODUG IN ANY FORM WITHOUT THE W CUSTOM CABLE INC. ACCEPTA	AWING MAY CONTAIN PATENTED OR ETARY INFORMATION AND MUST NOT BE USED IY PURPOSE DETRIMENTAL TO CUSTOM CABLE MAY NOT BE REPRODUCED OR TRANSCRIBED FORM WITHOUT THE WRITTEN CONSENT OF M CABLE INC. ACCEPTANCE OF THIS DRAWING JISHES AND AGREEMENT OF THE FOREGOING.		Title: SMA-RA-JK/MMCX-ST-JK G174 60I Part No: Q-2P0110003060I		