4-215915-0 - ACTIVE


AMP-LATCH

TE Internal #: 4-215915-0 Ribbon Cable Connectors, Wire-to-Board, 40 Position, 2.54 mm [.1 in] Centerline, 2 Row, Receptacle, Polarization Mating Alignment Type, Wire & Cable

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > FFC, FPC & Ribbon Connectors > Ribbon Cable Connectors



Connector System: Wire-to-Board

Number of Positions: 40

Centerline (Pitch): 2.54 mm [.1 in]

Row-to-Row Spacing: 2.54 mm [.1 in]

Number of Rows: 2

Features

Product Type Features

Connector Product Type

Connector System

Connector & Housing Type

Connector Assembly

Wire-to-Board

Receptacle

| Connector & Contact Terminates To | Wire & Cable |
|---|------------------|
| Configuration Features | |
| Number of Positions | 40 |
| Number of Rows | 2 |
| Body Features | |
| Primary Product Color | Gray |
| Contact Features | |
| Mating Square Post Dimension | .64 mm[.025 in] |
| Mating Pin Diameter | .64 mm[.025 in] |
| Wire Contact Termination Area Plating Thickness | 2.54 μm[100 μin] |
| Wire Contact Termination Area Plating Material | Tin |
| | 30 µin |
| Contact Mating Area Plating Material | Gold |
| Contact Current Rating (Max) | 1 A |

4-215915-0

Ribbon Cable Connectors, Wire-to-Board, 40 Position, 2.54 mm [.1 in] Centerline, 2 Row, Receptacle, Polarization Mating Alignment Type, Wire & Cable



| Termination Method to Wire & Cable | Insulation Displacement (IDC) |
|------------------------------------|-------------------------------|
| Mechanical Attachment | |
| Mating Alignment Type | Polarization |
| Mating Retention | Without |
| Connector Mounting Type | Cable Mount (Free-Hanging) |
| Housing Features | |
| Centerline (Pitch) | 2.54 mm[.1 in] |
| Dimensions | |
| Row-to-Row Spacing | 2.54 mm[.1 in] |
| Usage Conditions | |
| Operating Temperature Range | -65 – 105 °C[-85 – 221 °F] |
| Operation/Application | |
| Circuit Application | Signal |
| | |
| Product Compliance | |

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU

Compliant

| EU ELV Directive 2000/53/EC | Compliant |
|---|---|
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC |
| Halogen Content | Not Low Halogen - contains Br or Cl > 900 ppm. |
| Solder Process Capability | Not applicable for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides

4-215915-0

Ribbon Cable Connectors, Wire-to-Board, 40 Position, 2.54 mm [.1 in] Centerline, 2 Row, Receptacle, Polarization Mating Alignment Type, Wire & Cable



on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought





Documents

| Product Drawings | |
|--------------------------|--|
| AMP-LATCH 15.2 HIGH TAPE | |

English

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_4-215915-0_F.2d_dxf.zip English Customer View Model

ENG_CVM_CVM_4-215915-0_F.3d_igs.zip

4-215915-0

Ribbon Cable Connectors, Wire-to-Board, 40 Position, 2.54 mm [.1 in] Centerline, 2 Row, Receptacle, Polarization Mating Alignment Type, Wire & Cable



English

Customer View Model ENG_CVM_CVM_4-215915-0_F.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application of AMP-LATCH, Ribbon Cable Connectors

English

Application Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English