
## **CUSTOMER DRAWING**



	Component Dimensions				"GA"	Cable Dimensions				
Product	L	øΑ	øΒ	øС	Wire Gauge	øD	øΕ	øF	G±0.5	M±0.5
Name	max	min	min	min	(AWG)			min	(G±0.02)	$(M\pm0.02)$
B-044-24-2	29.0 (1.142)	3.40 (0.135)	2.30 (0.090)	0.8 (0.030)	24	1.70 (0.065) to 3.40 (0.135)	1.30 (0.050) to 2.30 (0.090)	0.30 (0.012)	16.0 (0.630)	6.0 (0.235)

## **MATERIALS**

- 1. & 5. INSULATION SLEEVE: Heat-shrinkable, radiation cross-linked modified polyvinylidene fluoride. Transparent blue.
- 2. & 4. SOLDER PREFORMS WITH FLUX:

SOLDER: TYPE Sn63 per ANSI J-STD-006.

FLUX: TYPE ROL0 per ANSI J-STD-004.

- 3. & 6. MELTABLE RINGS: Thermally stabilized thermoplastic.
- 7. . CONDUCTOR LEAD: RAYCHEM 55A0111 in accordance with MIL-W-22759/32. See table for AWG.ETFE insulated, stranded tin plated copper


Color: white.

 GROUND LEAD: RAYCHEM 55A0111 in accordance with MIL-W-22759/32. See table for AWG.ETFE insulated, stranded tin plated copper Color: blue.

## APPLICATION

- 1. The parts covered by this SCD are for use in terminating the primary conductor and the braided shield of a coaxial cable having tin or silver plated conductor and shield, rated for at least 125° C and meeting the dimensional requirements listed.
- 2. Parts will meet the requirements of Raychem Specification RT-1404 when installed per Raychem RPIP-500-03.
- 3. Temperature range:  $-55^{\circ}$ C to  $+150^{\circ}$ C.

For best results, prepare the cable as shown:



TE Connectivity, TE connectivity (logo), Raychem, and SolderSleeve are trademarks

= TE	pecified dimensions a	so in millimeters	<b>Raychem</b> Devices	COAXIAL SOLDERSLEEVE DEVICE WITH PRE-INSTALLED STRANDED WIRE				
	are shown in bracket  ANGLES: N/A	s]	erves the right to amend	B-044-24-2				
0.00 N/A 0.0 N/A 0 N/A			ime. Users should ty of the product for their	Revision : C	Issue Date : 01-DEC-2021			
DRAWN BY: MALLIKA D	CAGE CODE: 06090	DATE: 19-NOV-2021	ECN: ECN-21-128737	SCALE: NTS	SIZE:	SHEET: 1 of 1		