





APPLICATOR PARTS LIST


TYPE
SIDWISE STRAIN RELIEF WING

**AMP INCORPORATED
HARRISBURG, PENNA.**

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	
1	WIRE CRIMPER			42	SHEAR DEPRESSOR	1	810955-5	
2	INS. CRIMPER	1	453671-3	43	SPRING, SHEAR	1	386455	
3	ANVIL	1	453673-3	44	SPRING SEAT	1	386443	
4	ANVIL SPACER			45	SHEAR BEARING PL. FT.	1	386409-1	
5	SHEAR BLADE FLOATING	1	473243-2	46	REAR OILITE BEARING PL.	1	386408	
6	REAR SHEAR PLATE			47	LEFT OILITE BEARING PL.	1	386406	
7	SHEAR BLADE SPACER MT.	1	386442	48	RIGHT OILITE BEARING PL.	1	386407	
8	FRONT SHEAR PLATE	1	386414	49				
9	REAR ANVIL SPACER PLT.			50				
10	FRONT ANVIL SPACER PLT.			51	STRIP HOLD 	1	692871-1	
11	TOOL SPACER	1	370691	52				
12	CRIMP SPACER			53				
13	FRONT STRIP GUIDE	1	386444-3	54				
14	REAR STRIP GUIDE	1	386445	55				
15	RAM	1	473699	56				
16	TOOL HOLDER			57				
17	ADJ. CRIMP MOUNT			58				
18	ADJ. BLOCK			59				
19	APPLICATOR MOUNT ASSY.			60				
20	BASE PLATE	1	473228	61				
21	BASE BLOCK	1	473227	62				
22	STRIP GUIDE PLATE	1	473226	63				
23	ANVIL HOLDER			64	MECH FEED	1	692140-2	
24	AUX. ANVIL HOLDER			65	TENSION ADJ. PLATE	1	374999	
25	STRIPPER	1	694924-1	MISCELLANEOUS				
26	STRIPPER MOUNT			66	2 DIA REEL SUPPORT	1	565050-2	
27	RETAINER PLATE			67	LUBRICATOR ASSY	1	465184-2	
28	STRIPPER MOUNT BRACKET			68	SYNTHETIC OIL	1	22014-1	
29	STRIPPER BUSHING			69				
30	STOCK DRAG ASSY.	1	473229-1	70				
31	STOCK DRAG HANDLE			71				
32	STOCK DRAG STUD	1	388648-7	72				
33	STOCK DRAG SPRING	1	1-23847-1	REV.	0 REVISION RECORD 8-17-71	DATE	BY	ECN
34	STOCK DRAG ADJ. SCREW			A	PER ECN	1-24-72	RM	1-8680
35	FEED FINGER HOLDER			B	REV GUARD	10-1-74	W	2818
36	FEED FINGER	1	388477	C	INACTIVE FRG	2-24-77	CC	B R1983
37	FEED FINGER TIP	1	386447					
38	FEED FINGER SPACER GUIDE 	1	1-471716-3					
39	BASE CASTING	1	570238					
40	GUARD ASSY	1	461343-1					
41	LOWER GUARD	1	694454-1					

CRIMPING DATA			TERMINALS
TO APPLY TERMINAL			61987
WIRE SIZE	CRIMP HEIGHT	TILL TIGHT	
CRIMP	SIZE	TYPE	FEED
INSUL.	360	Q	.908
STEEL	DIAMOND		
INSULATION RANGE	WIRE RANGE		
.275-.290	---		
EXPLODED VIEW			
A-6009-3			
REMARKS:			
 MT. ON ITEM 14			
 MT. ON TOP SCREW OF SHEAR BEARING PL. 45			
TOP TOOL MT. 42, 11 & 2			

**— INACTIVE —
FOR REPLACEMENT ONLY**

<p>■ DENOTES WEARING PARTS RECOMMEND PURCHASE REPLACEMENT</p>			
<p>THIS APPLICATOR IS TO BE USED ON AMP-O-LECTRIC 1-471273-3 MECH FEED</p>			
SERIAL NO.		DATE SHIPPED	DESIGNED
			R.B.  8-17-71
CUSTOMER NAME AND ADDRESS			CHK'D
			1-24-71 8-14-11
APPLICATOR NUMBER			APPT'D
REV. B1	566053-2		2-24-71
SHEET			1 OF 1

FOR HARDWARE
SEE 687514-1