



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
02 <sub>1</sub>	REVISED	8/14/71	[Signature]

HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
CONTACT EXT	IRON-NICKEL ALLOY PER ASTM-F-30	GOLD PLATE PER MIL-G-45204
'O' RING	FLUOROCARBON RUBBER PER MIL-R-83428, TYPE 1, CLASS 1	N/A
HERMETIC SEAL	GLASS BEAD	N/A

COMPONENT	MATERIAL	FINISH
-----------	----------	--------

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES FRAC. ± 1/64 DEC. ± .005 ANGLES ± 1°	DRAWN BY	EJC	DATE	2/27/71	 AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
	CHECKED BY	PRB	DATE	3/8/71	
	APPD BY	BWC	DATE	3/8/71	

These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASSY PROCEDURE	TITLE "OSSM" HERMETICALLY SEALED STRAIGHT BULKHEAD JACK (THREADS REAR)		
	NO. A.P. N/A	SIZE	CODE IDENT NO.	REV
		B	26805	1058-3100-00
	SCALE	8:1	SHEET 1 OF 1	

NOTES:  
1. CAPTURED CENTER CONTACT

.XXX = in  
XX.X = mm (REF)