

Ratings

Voltage: 600 V
 Temperature: -40~105 °C
 Flammability: FT2

Conductor

Conductor count: 3
 Gauge: 28 AWG 0.09 mm²
 Material: tinned copper strands
 Strand size: $\phi 0.127 \times 7$
 Resistance at 20 °C: 250 Ω /km max

Insulator

Material: mPPE
 Color: red, black, white
 Diameter: $\phi 0.9 \pm 0.08$ mm
 Average thickness: 0.25 mm
 Resistance at 20 °C: 100 M Ω /km min

Wrap

Material: cotton paper



Outer jacket

Material: mPPE, 85A
 Color: black
 Diameter: $\phi 3.6 \pm 0.15$ mm
 Average thickness: 0.78 mm

Wire marking: E339579 UL AWM STYLE 21509 28 AWG 105°C
 600V --- cUL AWM I A 105°C 600V FT2 TENSILITY

Bend radius

Minimum: 6 times diameter (21.6 mm)



Revision:	Date:	Description:	Prepared:	Notes:	TENSILITY
A	5/5/2021	Initial release	AW <small>Digitally signed by AW Date: 2021.05.06 12:40:57 -07'00'</small>		
			Verified:	Phthalate and halogen free	tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
			Dimensions are in millimeters. Tolerances:	Description:	Size: Part number:
			X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Wire, 3C TS, 28 AWG, 21509, 600V, 105C, 3.6 mm, FT2, mPPE	A 30-01987
					Scale: 15:1 Sheet 1 of 1

5

4

3

2

1