

INTERNAL PART NUMBER	CATALOG NUMBER	UPC CODE	DESCRIPTION
00970026XP	097026	0 79458 03491	MAXI FUSE PULLER

1	914-238	LABEL, UPC	200	EA
1	914-796	LABEL, BAR CODE	10	EAD
1	580690	CARTON	10	EA
1	896-451	BOX	200	EA
1	890-330-149	CARD (INSERT)	1000	EA
1	896-468	BLISTER	1000	EA
1	00970026N	MAXI FUSE PULLER	1000	EA
NO	COMPONENT NO	DESCRIPTION	QTY/M	U/M

BILL OF MATERIAL	
CDPIES TO	MATL SPEC
1 9 18	DRW BJJ
2 10 19	DATE 9/24/98
3 12 20	SCALE
4 13 21	CHK
5 14 23	DATE
6 15 33	APPD
7 16 43	RAW STK WT
8 17 53	LBS/M
TOLERANCE UNLESS OTHERWISE SPECIFIED	
TWO PLACE DEC ±.01	
THREE PLACE DEC ±.005	
ANGULAR ±1°	
TITLE	
MAXI FUSE PULLER	
CHK	APD
07683 - RELEASED 9/24/98 BJJ	REVISION
80237C-CHG 896-436 TO 896-468 10/22/98 P.M	
80753C-CAD TO CHG 08/27/00 PJM	
DES PLAINES, ILL INOIS 60016	
Facebook	
Twitter	
LinkedIn	
YouTube	
00970026XP	FINAL

PLACE 1 MAXI FUSE PULLER 00970026N UNDER BLISTER 896-468 ON CARD 890-330-149 AND SEAL.

PLACE 5 CARDS IN BOX 896-451 AND LABEL, ON SMALLEST "END" PANEL, WITH 914-238 LABEL PRINTED TO GENERAL LABEL SPEC. LS-000001.

PLACE 20 PACKED BOXES IN OVERPACK CARTON 580690 AND SEAL WITH TAPE. LABEL END PANEL, IN LOWER RIGHT HAND CORNER, WITH 914-796 LABEL PRINTED TO GENERAL LABEL SPEC. LS-000003.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.

CPK DENOTES CRITICAL CHARACTERISTICS.

CPK DENOTES CPK DIMENSIONS - MINIMUM CPK VALUE

CPK DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION

OF PROCESS VARIATION TO BE USED IN THE INSPECTION PROCEDURE FOR MEASUREMENT

AND TOLERANCE TO BE USED IN THE INSPECTION PROCEDURE FOR MEASUREMENT

UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.

CPK DENOTES CP DIMENSIONS - MINIMUM CP VALUE

CPK DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION

OF PROCESS VARIATION TO BE USED IN THE INSPECTION PROCEDURE FOR MEASUREMENT

AND TOLERANCE TO BE USED IN THE INSPECTION PROCEDURE FOR MEASUREMENT

UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.

CPK DENOTES CP DIMENSIONS - MINIMUM CP VALUE

CPK DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION

OF PROCESS VARIATION TO BE USED IN THE INSPECTION PROCEDURE FOR MEASUREMENT

AND TOLERANCE TO BE USED IN THE INSPECTION PROCEDURE FOR MEASUREMENT

UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.

CPK DENOTES CP DIMENSIONS - MINIMUM CP VALUE

CPK DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION

OF PROCESS VARIATION TO BE USED IN THE INSPECTION PROCEDURE FOR MEASUREMENT

AND TOLERANCE TO BE USED IN THE INSPECTION PROCEDURE FOR MEASUREMENT

