



Material: Nylon 66 UL 94V-0

### Ordering Code

CI15    \*\*    S    0000  
 ①    ②    ③    ④

- ① Series No.
- ② No. of Circuits:
- ③ S= Connector housing
- ④ Color option: 0000= Nature (Standard)

Circuits	Dimension		
	A	B	C
2	1.50(.059)	3.5(.138)	4.50(.177)
3	3.00(.118)	5.0(.196)	6.00(.236)
4	4.50(.177)	6.5(.255)	7.50(.295)
5	6.00(.236)	8.0(.314)	9.00(.354)
6	7.50(.300)	9.5(.374)	10.50(.413)
7	9.00(.354)	11.0(.433)	12.00(.472)
8	10.50(.413)	12.5(.492)	13.50(.531)
9	12.00(.472)	14.0(.551)	15.00(.591)
10	13.50(.531)	15.5(.610)	16.50(.650)
11	15.00(.590)	17.0(.669)	18.00(.709)
12	16.50(.649)	18.5(.728)	19.50(.768)
13	18.00(.708)	20.0(.787)	21.00(.827)
14	19.50(.767)	21.5(.846)	22.50(.886)
15	21.00(.826)	23.0(.905)	24.00(.945)

**Halogen-Free**    **RoHS Compliant**

CVILUX.CORP  
**2006.12.28**  
**ISSUED**

④					DATE	UNIT: mm / inch	TITLE: 1.50MM(.024")	瀚荃股份有限公司 CviLux Corporation	
③				DRAWN BY: Hank	12/22-06'	TOLERANCE UNLESS OTHERWISE SPECIFIED	CRIMP TERMINAL HOUSING		
②				ENGINEER: Eisley	12/22-06'	.X ± 0.30/.012    X' ± 1"	MATERIAL:	DRAWING NO. <b>CI1512SA</b> PART NO. <b>CI15**S0000</b>	
①				CHECKED BY: David	12/22-06'	.XX ± 0.20/.008    .X' ±	FINISH:		
SYM	NAME	DATE	REVISIONS	APPROVED BY: Alex	12/22-06'	.XXX ± 0.10/.004    .XX' ±	SCALE	6 / 1	
								SHEET	1 OF 1