



Fuse, Dimensions: 6.3x32 mm, Trigger characteristic: Slow-acting (T); Rated voltage: 500 / 440 / 250 V, Rated current: 5 A

Business data

Article number	4967.0
Article name	SI 6,3x32 5,000A-T
GTIN (EAN)	4044211109295
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	2.66 g
Weight per piece (including packaging)	2.7 g
Unit of weight	G
Customs number	85361010
Country of origin	EU
Product description	fuse

Technical data

Dimensions

Length	31.8 mm
Diameter of contact cap	6.35 mm
Dimensions	6,3x32 mm

Ratings

Rated voltage	500 / 440 / 250 V
Rated current	5 A

Materials

Contact caps	Brass
Surface	Nickel
Tube	Ceramic

Further technical data

Trigger characteristic	Time-lag (T)
Rated breaking capacity	1,5 kA @ AC 500 (cos ϕ = 1 10 kA @ AC 440 V cos ϕ = 0,3)
Voltage drop	135 mV
Power loss (@ 1.5 In)	2.2 W
Melting integral I ² t _s	80 A ² s

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-01-17
REACH Candidate Substance Note	No
RoHS Conform	yes

Data sheet

4967.0 SI 6,3x32 5,000A-T



Media

Accessories
