




In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C ⁽¹⁾	STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C ⁽²⁾
RATING	VOLTAGE	100 V AC ⁽³⁾		OPERATING HUMIDITY RANGE	40 % TO 80 %
	CURRENT	0.5 A ⁽³⁾		STORAGE HUMIDITY RANGE	40 % TO 70 % ⁽²⁾
	APPLICABLE CABLE		AWG 36.40 THIN COAXIAL CABLE 		
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION	VISUALLY AND BY MEASURING INSTRUMENT.				
GENERAL EXAMINATION	CONFIRMED VISUALLY.				
MARKING			x	x	
			x	x	

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
 2	DIS-F-001927	KN. SHIBUYA	HT. YAMAAGUCHI	07.05.11
REMARKS ⁽¹⁾ INCLUDE TEMPERATURE RISE CAUSED BY CURRENT-CARRYING. ⁽²⁾ "STORAGE" MEANS A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE ASSEMBLY TO PCB. ⁽³⁾ IT IS THE MAXIMUM VALUE OF CONNECTOR. CONFIRM THE SPECIFICATION OF THE CABLE. Unless otherwise specified, refer to JIS-C-5402.				
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.		ELC4-156658-00

HRS	SPECIFICATION SHEET	PART NO.	FX15S-51P-GND	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL575-2117-2-00	 1/1