



注記
NOTE

- 1 ウエハーのそりは、長さ 25.4 に対して 0.24 MAX..
CAMBER MUST BE 0.24 MAX. PER 25.4
- △ 全極数が偶数の場合のみ適用。
TO BE APPLIED ONLY WHEN ALL CKTS. ARE EVEN.

49.72	45.72	10-32-1101	5281-10A	10
44.64	40.64	▲ -1091	▲ -09A	9
34.48	30.48	-1071	-07A	7
29.4	25.4	-1061	-06A	6
24.32	20.32	-1051	-05A	5
19.24	15.24	-1041	-04A	4
14.16	10.16	▼ -1031	▼ -03A	3
9.08	5.08	10-32-1021	5281-02A	2
B	A	EDP NO.	ENG. NO.	極数 NO. OF CKTS.

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS	SCALE	CURRENT REV DESC:					
mm	4:1	 KK 5.08 WAFER ASSY WITH LOCK PRODUCT CUSTOMER DRAWING					
GENERAL TOLERANCES (UNLESS SPECIFIED)					EC NO: 620398	2018/12/21	DOCUMENT NUMBER
4 PLACES	±				DRWN: AKUMAR19	2018/10/18	SD-5281-001
3 PLACES	±				CHK'D: GGA	2019/10/18	DOC TYPE
2 PLACES	±				APPR: GGA	2019/10/18	PSD
1 PLACE	±	INITIAL REVISION:		DOC PART			
0 PLACES	±	DRWN: TYAJIMA01	2014/03/13	001			
ANGULAR TOL ± 1.0°		APPR: NUKITA	2014/03/13	J			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SHEET NUMBER			
			A3-SIZE	1 OF 1			
		SERIES	MATERIAL NUMBER	CUSTOMER			
		5281	SEE TABLE	GENERAL MARKET			

GENERAL TOLERANCES (UNLESS SPECIFIED)		
10 UNDER	±0.15	
10 OVER 30 UNDER	---	
30 OVER	---	