



General ordering data

| | |
|------------------|--|
| Order No. | 1805770000 |
| Part designation | SFC 2/21 NEUTRAL BL |
| Version | Conductor markers, L x W: 21 x 4 mm, Polyamide, Blue |
| EAN | 4032248273508 |
| Qty. | 120 pc(s). |

Markings

| | |
|--|-----------------------------|
| Cadmium | no |
| Can be labelled with thermal transfer printers | No |
| Can be printed with plotter | Yes |
| Can be written with dot-matrix printer | No |
| Can be written with laser printer | No |
| Conductor O.D., max. | 5 mm |
| Conductor O.D., min. | 3 mm |
| Conductor cross-section, max. | 4 mm ² |
| Conductor cross-section, min. | 2.5 mm ² |
| Function | Conductor and cable markers |
| Halogen | no |
| Height | 7 mm |
| Insulation cross-section, max. | 5 mm |
| Length | 21 mm |
| Material | Polyamide |
| Material colour | Blue |
| Material colour according to resistance code | 6 |
| Max. temperature, continuous | 100 °C |
| Min. temperature, continuous | -40 °C |
| Pin can be written (STI) | Yes |
| PrintJet | Yes |
| Printed characters | without |
| Silicone | no |
| Speed marking laser | Yes |
| Type of printing | Neutral |
| UL 94 flammability class | V2 |

Markings

Width 4 mm

Approvals

Approvals institutes **n.a.**

Classifications

| | |
|------------|-------------|
| ETIM 2.0 | EC001530 |
| ETIM 3.0 | EC001530 |
| eClass 4.1 | 24-19-02-19 |
| eClass 5.0 | 27-14-91-03 |
| eClass 5.1 | 27-14-91-03 |

Similar products

| Order No. | Part designation | Version |
|------------|---------------------|--|
| 1813220000 | SFC 0/21 NEUTRAL BL | Conductor markers, L x W: 21 x 4 mm, Polyamide, Blue |
| 1779080002 | SFC 1/21 NEUTRAL BL | Conductor markers, L x W: 21 x 4 mm, Polyamide, Blue |
| 1025300000 | SFC 3/21 MC NE BL | Conductor markers, L x W: 21 x 4 mm, Polyamide, Blue |