

Component Video with Stereo Audio over Cat5/Cat6 Extender, Wallplate Remote Receiver, Up to 700-ft.

MODEL NUMBER: **B136-100-WP-1**



Highlights

- Remote extender wallplate for the B136-004 4-Port Extender/Splitter
- Extends a 1080i (60Hz) Component Video and Stereo Audio signal up to 300 ft. when using 24Awg, Solid Wire UTP cable
- Tripp Lite N022-01K-GY or N222-01K-GY; or, up to 400 ft. when using Zero-Skew UTP cable (Tripp Lite P524-01K)
- RJ45 Jack rear connection
- No external power required

Package Includes

- B136-100-WP-1 Component Video + Stereo Audio Remote Extender Wallplate
- Wallplate Mounting Screws
- Owner's Manual

Description

The B136-100-WP-1 is a remote extender wallplate for the B136-004, 4-Port Component Video + Audio Extender/Splitter. A 1080i (60Hz) Component Video and Stereo Audio signal can be extended up to 300 ft. when using 24Awg, Solid Wire UTP cable (Tripp Lite N022-01K-GY or N222-01K-GY); or, up to 400 ft. when using Zero-Skew UTP cable (Tripp Lite P524-01K). A 480p (60Hz) Component Video and Stereo Audio signal can be extended up to 500 ft. when using 24Awg, Solid Wire UTP cable (Tripp Lite N022-01K-GY or N222-01K-GY); or, up to 700 ft. when using Zero-Skew UTP cable (Tripp Lite P524-01K). No external power required.

Features

- Remote extender wallplate for the B136-004 4-port Extender/Splitter
- RJ45 Jack rear connector
- A 1080i (60Hz) Component Video and Stereo Audio signal can be extended up to 300 ft. when using 24Awg, Solid Wire UTP cable (Tripp Lite N022-01K-GY or N222-01K-GY); or, up to 400 ft. when using Zero-Skew UTP cable (Tripp Lite P524-01K)
- No external power required

Specifications

| OVERVIEW | |
|--------------|-------------------------|
| UPC Code | 037332162892 |
| Product Type | Cat5/Cat6 Receiver |
| Technology | Component; Stereo Audio |

| VIDEO | |
|-------------------------------------|-------------------------|
| Max 720P Range (ft) | 400 |
| Maximum Signal Range (ft) | 700 |
| Maximum Signal Range (m) | 213 |
| PHYSICAL | |
| Color | White |
| Shipping Dimensions (hwd / in.) | 2.50 x 3.00 x 5.00 |
| Shipping Dimensions (hwd / cm) | 6.35 x 7.62 x 12.70 |
| Shipping Weight (lbs.) | 0.30 |
| Shipping Weight (kg) | 0.14 |
| COMMUNICATIONS | |
| Max 1024 x 768 Range (ft) | 700 |
| Max 480P Range (ft) | 700 |
| Max 1440 x 900 Range (ft) | 400 |
| Max 1080i Range (ft) | 400 |
| Max 480i Range (ft) | 700 |
| Max 640 x 480 Range (ft) | 700 |
| Max 800 x 600 Range (ft) | 700 |
| Max 1600 x 1200 Range (ft) | 400 |
| CONNECTIONS | |
| Number of Ports | 1 |
| Side A - Connector 1 | (5) RCA (FEMALE) |
| Side B - Connector 1 | RJ45 (FEMALE) |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | 1-year limited warranty |