

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		TEST METHOD		REQUIREMENTS		Q	AT
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C (1)	STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C (2)			
	VOLTAGE	100 V AC	OPERATING HUMIDITY RANGE	40 % TO 80 %			
	CURRENT	0.5 A	STORAGE HUMIDITY RANGE	40 % TO 70 % (2)			
SPECIFICATIONS							
ITEM	TEST METHOD		REQUIREMENTS		Q	AT	
CONSTRUCTION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		X	X
GENERAL EXAMINATION		CONFIRMED VISUALLY.				X	X
ELECTRIC CHARACTERISTICS							
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).		40 mΩ MAX.		X		-
CONTACT RESISTANCE	20 mV MAX, 1 mA(DC OR 1000Hz)		50 mΩ MAX.		X		-
MILLIVOLT LEVEL METHOD							
INSULATION RESISTANCE	250 V DC		100 MΩ MIN.		X		-
VOLTAGE PROOF	300 V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.		X		-
MECHANICAL CHARACTERISTICS							
MECHANICAL OPERATION	100 TIMES INSERTIONS AND EXTRACTIONS.		① CONTACT RESISTANCE: 50 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X		-
VIBRATION	FREQUENCY 10 TO 55 Hz. AMPLITUDE : 1.5 mm. 2 hrs IN 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X		-
SHOCK	490 m/s ² , DURATION OF PULSE 11 ms FOR 3 TIMES IN 3 DIRECTIONS.				X		-
ENVIRONMENTAL CHARACTERISTICS							
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 hrs.		① CONTACT RESISTANCE: 50 mΩ MAX. ② INSULATION RESISTANCE: 100 MΩ MIN.		X		-
RAPID CHANGE OF TEMPERATURE	TEMPERATURE: -55 → +15 ~ +35 → +85 → +15 ~ +35 °C TIME 30 → MAX 5 → 30 → MAX 5 min 5 CYCLES.		③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X		-
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 hrs.		① CONTACT RESISTANCE: 50 mΩ MAX. ② NO HEAVY CORROSION.		X		-
HYDROGEN SULPHIDE	EXPOSED IN 3 PPM FOR 96 hrs. (TEST STANDARD: JEIDA 38)				X		-
RESISTANCE TO SOLDERING HEAT	1) REFLOW SOLDERING : 250 °C MAX, : 220 °C MIN, FOR 60 s 2) SOLDERING IRONS : 360 °C, FOR 5 s		NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.		X		-
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE: 240 °C, FOR IMMERSION DURATION, 3 sec.		A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSERD.		X		-
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE			
△							
REMARK (1) TEMPERATURE RISE INCLUDED WHEN ENERGIZED. (2) THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED. Unless otherwise specified, refer to MIL-STD-1344.							
Note QT: Qualification Test AT: Assurance Test X: Applicable Test		DRAWING NO.	ELC4-071326-25				
HRS	SPECIFICATION SHEET	PART NO.	FX6A-60P-0.8SV2 (71)				
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL576-0245-8-71				1/1
		APPROVED	HS. OKAWA	06.11.01			
		CHECKED	HS. OZAWA	06.11.01			
		DESIGNED	TK. YANAGISAWA	06.09.09			
		DRAWN	TK. YANAGISAWA	06.09.09			