

RSM-8 24V- 1CO S

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com



Similar to illustration

Relay bases (RSM) with common positive and negative to be connected to PLC or other type of controllers. The interfaces are made up of groups of 4, 8 or 16 RCL relays (12.7 mm) or RSS (6.1 mm). The connection to the controller can be set up using pluggable connectors or using direct cabling with IEC 60603-13 connectors. Wide range of options:

- 1 or 2 CO contacts with 16/8/6 A relays
- Voltages from 5 to 230 V
- Screw, tension clamp or PUSH IN connection
- Compatible with Weidmüller's solid-state relays

The range of relays provides galvanic isolation between input/output as well as between the adjacent contacts on the relays. This enables the various voltages in the controllers and those required by the various field elements to be safely adapted.

General ordering data

Version	Interface, RSM, Screw connection
Order No.	1447880000
Type	RSM-8 24V- 1CO S
GTIN (EAN)	4050118252316
Qty.	1 pc(s).

RSM-8 24V- 1CO S

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

Technical datawww.weidmueller.com**Dimensions and weights**

Depth	66 mm	Depth (inches)	2.598 inch
Height	87 mm	Height (inches)	3.425 inch
Width	130 mm	Width (inches)	5.118 inch
Net weight	321 g		

Temperatures

Storage temperature	-40...60 °C	Operating temperature	-25...50 °C
---------------------	-------------	-----------------------	-------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1, 4,4'-isopropylidenediphenol 80-05-7	SCIP	66e752f3-a24f-4fef-89c4-f29f52d01390
------------	---	------	--------------------------------------

General data

LED status display per relay	green	LED status of the supply voltage	yellow
------------------------------	-------	----------------------------------	--------

Connection data

Connection (field side)	LL 5.08 mm	Connection on control side	LP 5.08 + plug-in connector in acc. with IEC60603-13 / DIN41651, 10-pin, LL 5.08 mm
-------------------------	------------	----------------------------	---

Rating data

Mechanical service life	30 x 10 ⁶ switching cycles
-------------------------	---------------------------------------

Ratings data input

Input voltage	24 V DC ± 10%	Input current	16.7 mA
---------------	---------------	---------------	---------

Ratings data output

Relay type	RCL	Type of output	Potential-free contact
Contact material	AgNi 90/10	Rated voltage	≤ 250 V AC
Max. AC continuous current	6 A	Minimum contact current	0.1 A
Minimum contact voltage	5 V		

Insulation coordination (EN50178)

Pollution severity level	2	Pulse voltage test (1,2/50µs)	6 kV
Insulation test voltage	1.2 kVAC		

Insulation coordinates (EN50178)

Rated input insulation voltage	< 50 V AC	Rated output insulation voltage	250 V AC
Overvoltage category input/output	III	Overvoltage category output/output	II
Pollution severity level	2	Pulse voltage test (1,2/50µs)	6 kV
Insulation test voltage	1.2 kVAC	Clearance input/output	≥ 5.5 mm

RSM-8 24V- 1CO S

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

Technical data

info@weidmuller.com
www.weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com
info@weidmuller.com

Connection field

Clamping range, max.	6 mm ²
Flexible with sleeve, max.	2.5 mm ²
Flexible, max. H05(07) V-K	4 mm ²
Max. wire cross-section, AWG	AWG 12
Sleeve with plastic collar, max.	2.5 mm ²
Solid, min. H05(07) V-U	0.5 mm ²
Tightening torque, max.	0.6 Nm
Type of connection	Screw connection

Clamping range, min.	0.5 mm ²
Flexible with sleeve, min.	0.5 mm ²
Flexible, min. H05(07) V-K	0.5 mm ²
Min. wire cross-section, AWG	AWG 26
Solid, max. H05(07) V-U	6 mm ²
Stripping length	6 mm
Tightening torque, min.	0.5 Nm

Classifications

ETIM 6.0	EC002780	ETIM 7.0	EC002780
ETIM 8.0	EC002780	ECLASS 9.0	27-14-11-52
ECLASS 9.1	27-24-22-16	ECLASS 10.0	27-14-11-52
ECLASS 11.0	27-14-11-52	ECLASS 12.0	27-14-11-52

Approvals

Approvals



ROHS	Conform
Certificate No. (cURus)	E141197

Downloads

Approval/Certificate/Document of Conformity	Declaration of Conformity
Product Change Notification	20210506 Technical change to RSM modules
Catalogues	Catalogues in PDF-format
Brochures	

Data sheet

RSM-8 24V- 1CO S

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

Drawings

