

PSR-TRISAFE STARTER KIT - Starter kit



2986300

<https://www.phoenixcontact.com/us/products/2986300>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



STARTER kit for the PSR-TRISAFE safety module consisting of: PSR-TRISAFE demoboard (with inputs & outputs), SAFECONF CD, Quick Start Guide, USB cable (3m) , voltage supply with international connector adapters and package inserts.

Your advantages

- Prewired starter kit including quick start guide
- Easy introduction to configurable safety technology

Commercial data

| | |
|--------------------------------------|--------------------------------|
| Item number | 2986300 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Note | Made to order (non-returnable) |
| Sales key | DN02 |
| Product key | DNA353 |
| Catalog page | Page 261 (C-6-2019) |
| GTIN | 4046356503907 |
| Weight per piece (including packing) | 5.1 kg |
| Weight per piece (excluding packing) | 3.6 kg |
| Customs tariff number | 90230080 |
| Country of origin | DE |

PSR-TRISAFE STARTER KIT - Starter kit



2986300

<https://www.phoenixcontact.com/us/products/2986300>

Set consists of

PSR-SAFECONF-BOX-DE - Configuration package

2986151

<https://www.phoenixcontact.com/us/products/2986151>

Configuration package for the PSR-TRISAFE safety module, consisting of the SAFECONF software, connecting cable and Quick Start Guide.



PSR-SAFECONF-BOX-EN - Configuration package

2986164

<https://www.phoenixcontact.com/us/products/2986164>

Configuration package for the PSR-TRISAFE safety module, consisting of the SAFECONF software, connecting cable and Quick Start Guide.



PSR-TRISAFE STARTER KIT - Starter kit



2986300

<https://www.phoenixcontact.com/us/products/2986300>

CABLE-USB/MINI-USB-3,0M - USB cable

2986135

<https://www.phoenixcontact.com/us/products/2986135>

USB connecting cable: USB plug type A to USB plug type Mini-B; length: 3 m



PSR-SCP- 24DC/TS/M - Safety module

2986012

<https://www.phoenixcontact.com/us/products/2986012>



Freely configurable safety module with 20 safe inputs and 4 safe outputs; 4 alarm, 2 clock, and 2 ground switching outputs; can be extended with additional I/O modules, up to SIL 3, Cat.4/PL e, SIL 3, EN 50156, plug-in screw connection terminal blocks

PSR-TRISAFE STARTER KIT - Starter kit



2986300

<https://www.phoenixcontact.com/us/products/2986300>

Technical data

Product properties

| | |
|--------------|-------------|
| Product type | Starter kit |
|--------------|-------------|

Electrical properties

| | |
|---|-----|
| Maximum power dissipation for nominal condition | 3 W |
|---|-----|

Dimensions

| | |
|--------|---------|
| Width | 37.5 mm |
| Height | 17 mm |
| Depth | 38 mm |

PSR-TRISAFE STARTER KIT - Starter kit



2986300

<https://www.phoenixcontact.com/us/products/2986300>

Classifications

ETIM

| | |
|----------|----------|
| ETIM 7.0 | EC001449 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39122205 |
|-------------|----------|

PSR-TRISAFE STARTER KIT - Starter kit



2986300

<https://www.phoenixcontact.com/us/products/2986300>

Environmental product compliance

| | |
|------------|--|
| China RoHS | Environmentally Friendly Use Period = 50 years For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |
|------------|--|

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com