



15W Single Port Power-over-Ethernet Midspan IEEE802.3AF Compliant Power Injector



Features

- Compliant with IEEE802.3af Standard
- Non-Vented Case
- Small case size
- 1 Year Warranty
- Gigabit data rates
- Full Protection OCP, OVP
- Low Cost

Applications

- IP Telephones
- Wireless Network Access Points
- Security Cameras

Safety Approvals

- cUL/UL 60950-2
- IEC/EN 60950-2
- CE
- LPS

Mechanical Characteristics

- Length: 106mm (4.17in)
- Width: 40mm (1.57in)
- Height: 27mm (1.1in)
- Weight: 100g (3.5oz.)

Output Specifications

| Model | Input Connector | DC Output Voltage | Load | | Regulation | | Output Power |
|------------|-----------------|-------------------|------|--------|------------|------|--------------|
| | | | Min | Max | Line | Load | |
| POE15M-1AF | C6 | 56V | 0A | 0.275A | ±5% | | 15.4W |
| POE15W-1AF | C8 ¹ | 56V | 0A | 0.275A | ±5% | | 15.4W |

Notes: 1. C8 is polarized, however non-polarized cables can be used. The internal circuit does not require polarization.

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at www.phihong.com for the most up-to-date specifications and contact information.

INPUT:**AC Input Voltage Range**

90 to 264VAC

AC Input Voltage Rating

100 to 240VAC

AC Input Current

0.5A (RMS) max for 90VAC

0.35A (RMS) max for 240VAC

Leakage Current

0.25mA max @ 254VAC 50Hz

AC Input Frequency

47-63Hz

AC Inrush Current

30A (RMS) max for 115VAC

60A (RMS) max for 230VAC

OUTPUT:**Total Output Power**

15.4W

Ripple and Regulation

200mV max @25°C, 115VAC, 60Hz &

230VAC, 50Hz

Hold-up time:

16mS min at max load and 120VAC, 60Hz

ENVIRONMENTAL:**Temperature**

Operation -20°C to +50°C

Non-operation -25°C to +70°C

Humidity 5 to 90%

EMC

FCC Part 15 Class B

EN55022 Class B

Immunity EN50082-1

ESD: EN61000-4-2. Level 3

RS: EN61000-4-3. Level 2

EFT: EN61000-4-4. Level 2

Surge: EN61000-4-5. Level 3

CS: EN61000-4-6. Level 2

Voltage Dips EN61000-4-11

Harmonic: EN61000-3-2 Class A

Isolation TestPrimary to Secondary: 3000VAC for 1 second
10mA**Insulation Resistance**

Primary to Secondary: >10M OHM 500VDC

FEATURES:**Over Voltage/Current/Short Circuit Protection**

The output is equipped with short-circuit protection and overload protection as per the IEEE802.3af specification and conforms to UL60950-2. The output can be shorted permanently without damage.

Indicator

Solid Green: unit has detected a valid IEEE802.3af load

Blinking Green: Power "ON" active with no load

Blinking Green/Solid Red: Over load condition

Blinking Red/ Solid Green: Invalid load

Data in/Output Connector

RJ45

E option = Earth grounded shielded Rj45 connectors

Output Connection

+pin 3,6 / -pins 1,2

