



# Temperature & Humidity Sensor

## E9T-THS

The ILLUMRA Temperature & Humidity Sensor brings wireless, battery-free sensing in a discreet, low-maintenance package. The sensor is completely self-powered by harvesting ambient solar energy so there are no wires to run or batteries to replace, reducing installation time and eliminating the need for ongoing maintenance.

Use as part of a wireless control system to reduce energy consumption or to implement compliance with the latest energy regulations.

- Easily mounted to vertical walls using included adhesive pad, or use included stand to place on a horizontal surface
- Launch scenarios based on temperature and humidity
- Periodically measures temperature and humidity; Significant changes in readings are reported immediately

### Typical Applications

The sensor is useful in any situation where automatic temperature and humidity control will save energy.

- Homes
- Offices
- Wine cellars
- Hospitality
- Bathrooms
- Storage rooms
- HRV
- ERV

- **Interoperable.** Communicates wirelessly with other devices using the EnOcean wireless standard.
- **Maintenance Free.** Integrated solar cell harvests indoor light to power the sensor and eliminates the needs for wires or batteries. Optional battery tray for dark area use.
- **Easy installation.** Adhesive mounting, optional stand, along with the wireless and discreet design allow for versatile placement of the sensor.



### SPECIFICATIONS

<b>Power supply</b>	Primary: Indoor light energy harvesting via solar cell Backup: Optional battery (CR1225, not included)
<b>RF Communications</b>	EnOcean® Protocol 902 MHz
<b>Transmission range</b>	50-150 feet (typical)
<b>EEP (EnOcean Equipment Profile)</b>	EEP A5-04-03 / STM 350U
<b>Temperature sensor performance</b>	Measurement range: -4° to +140°F (-20° to +60°C) (10 bit resolution) Accuracy typ. ±0.3K
<b>Humidity sensor performance</b>	Measurement range: 0-100% rh (relative humidity), Accuracy typ. ±3% rh between 20% rh and 80% rh
<b>Measurement cycle time</b>	Once every 100s
<b>Threshold for immediate transmission</b>	Change by >±0.5K or >±1% rh versus last transmission
<b>Sign-of-life with measurement data update</b>	Once every 10-24 minutes (random)
<b>Charge time before linking</b>	Typ. 2.5 min @ 400 lux or 4 min @ 200 lux
<b>Operation time in darkness</b>	Typ. 4 days
<b>Dimensions of housing (without stand)</b>	2.99 x 0.83 x 0.55 inches (76 x 21 x 14 mm)
<b>Dimensionsof stand</b>	1.18 x 1.18 x 0.05 inches (30 x 30 x 1.2 mm) without side flap
<b>Operating conditions</b>	-4° to +140°F (-20° to +60°C) 0-93% rh, non-condensing IP 40, indoor use only
<b>Storage conditions (recommended)</b>	50° to 86°F (10° to 30°C), <60% rh, max. 36 months
<b>Agency Compliance</b>	FCC, ISED

115 S State St, Suite B  
Lindon, UT 84042

T: (801) 349-1200  
F: (801) 614-7100  
Sales@ILLUMRA.com

This device or certain aspects thereof is protected by at least one U.S. or International patent or has at least one such patent application pending.

ILLUMRA is a trademark of Ad Hoc Electronics, LLC. Other trademarks herein are the property of their respective owners.

AHD0642A