SPECIFICATION CONTROL DRAWING

CHEMINAX

50 OHM, AWG 12, 7 STRANDS OF .0296, COAXIAL CABLE

Date: Revision:

5012M3612

THIS SPECIFICATION SHEET FORMS A PART OF THE LATEST ISSUE OF RAYCHEM SPECIFICATION 1200.

CONSTRUCTION DETAILS

ELECTRICAL CHARACTERISTICS

DIMENSIONS ARE NOMINAL VALUES IN INCHES, UNLESS OTHERWISE DESIGNATED.

CHARACTERISTIC IMPEDANCE

50 ± 2 ohms, Method A

CAPACITANCE

25.0 pF/ft. (minimum), 30.0 pF/ft. (maximum)

VELOCITY OF PROPAGATION

78% (nominal)

ATTENUATION

3 dB/100 ft. (maximum) at 100 MHz

6 dB/100 ft. (maximum) at 400 MHz 10 dB/100 ft. (maximum) at 1 GHz

20 dB/100 ft. (maximum) at 3 GHz

CONDUCTOR .0890 AWG 12, 7 Strands of .0296. Silver-Coated Copper **DIELECTRIC** .234 Rayfoam L

Color - Natural

1st SHIELD

AWG 36.

2nd SHIELD

JACKET

AWG 36.

Silver-Coated Copper

Silver-Coated Copper

Radiation-Crosslinked,

Modified ETFE

ADDITIONAL REQUIREMENTS

ELECTRICAL

CONDUCTOR RESISTANCE

1.76 ohms/1000 ft. (nominal)

INSULATION RESISTANCE

10,000 megohms (minimum)

for 1000 ft.

JACKET FLAWS

SPARK TEST IMPULSE TEST

1.0 kV (rms) 6.0 kV (peak)

VOLTAGE WITHSTAND

(DIELECTRIC)

3500 volts rms)

225°C

ENVIRONMENTAL

FLAMMABILITY

FAR, Part 25 (Spec 1200, Method B)

HEAT SHOCK

LOW TEMPERATURE-

COLD BEND

-55°C/8.00 inch mandrel

VOLTAGE WITHSTAND

(Post Environmental)

1000 volts (rms), 1 minute

PHYSICAL

DIELECTRIC CONCENTRICITY

75% (minimum)

ELONGATION

INSULATION (DIELECTRIC)

50% (minimum)

TENSILE STRENGTH

1000 lbf/in² (minimum)

ELONGATION TENSILE STRENGTH 50% (minimum) 5000 lbf/in² (minimum)

JACKET THICKNESS

.010 inch (nominal)

SHIELD COVERAGE (each)

90% (minimum)

Outer jacket color will be black (designated by a "-0" appended to the part number, e.g. 5012M3612-0), unless otherwise specified.

Designate outer jacket color with a dash number in accordance with MIL-STD-681. Other codes and suffixes may be added to the part number, as necessary, to capture any additional requirements imposed by the purchase order.

WEIGHT

68.2 lbs/1000 ft. (nominal)

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics Corporation also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

Page 1 of 1

.255

.276

.296

Rayfoam, Cheminax, Raychem, TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks

