1090079

https://www.phoenixcontact.com/us/products/1090079



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Label, Roll, silver, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: adhesive, lettering field size: 70 x 32 mm, Number of individual labels: 750

Your advantages

- EML-LPR ... self-adhesive device markers for identification of various types of equipment in controller, system, and control cabinet building
- The EML-LPR labels feature a protective laminate, which is adhered to the entire printing surface after the label has been attached. The printed information is protected from external influences
- The protective laminate is attached to the label. The edge is perforated, simplifying adhesion
- · Thanks to its great adhesive strength, this label can be placed on rough, textured, and low-energy surfaces
- · High-quality printing is achieved in combination with the THERMOMARK-RIBBON 110 ink ribbon

Commercial data

Item number	1090079
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BG16
Product key	BG2411
GTIN	4055626897295
Weight per piece (including packing)	861 g
Weight per piece (excluding packing)	861 g
Customs tariff number	39199080
Country of origin	DE

1090079

https://www.phoenixcontact.com/us/products/1090079



Technical data

Product properties

Product type	Device marking	
Marking		
Number of individual labels	750	
Number of individual labels per row	1	
Mounting		
Mounting type	adhesive	

Material specifications

RoHS compliant	yes
Color	silver
Material	Polyester
Components	free from silicone and halogen

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish		
Result	Test passed	
UV resistance		
Specification	ISO 4892-2:2013-03 (following)	
Result	Test passed	
Test duration	96 h	

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-1):2011-07
	DIN EN 62208 (VDE 0660-511):2012-06 (in parts)

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed

Ambient conditions


Ambient temperature (operation)	-40 °C 150 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	23 °C

1090079

https://www.phoenixcontact.com/us/products/1090079

	PHŒNIX CONTACT	
Ľ	CONTACT	

	Recommended humidity (storage/transport)	50 %	
	Shelf life	2 years	
Dimensions			
	Width	70 mm	
	Length	32 mm	
Standards and regulations			
	Wipe resistance	DIN EN 61010-1 (VDE 0411-1)	
Notes			
	General	For the THERMOMARK ROLL and THERMOMARK ROLL 2.0 roll printers, this material can only be processed with an external media hub.	
	General	Items are approved for smooth and textured stainless-steel surfaces as well as for surfaces that have been coated with hammer-finish paint.	




https://www.phoenixcontact.com/us/products/1090079



Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1090079





https://www.phoenixcontact.com/us/products/1090079




Classifications

ECLASS

ECLASS-11.0	27281103
ECLASS-12.0	27281103
ECLASS-13.0	27281103

ETIM

	ETIM 8.0	EC001288	
UN	UNSPSC		
	UNSPSC 21.0	39131500	



https://www.phoenixcontact.com/us/products/1090079



Accessories

THERMOMARK ROLLMASTER 300 - Thermal transfer printer

0804501 https://www.phoenixcontact.com/us/products/0804501



Thermal transfer printer for material off the roll, incl. Euro/US power cable and USB cable. Support CD includes user manuals in several languages, links to firmware, drivers, and planning and marking software. Operating instructions printed in German and English. 1 roll of labels EML (20x8)R white = 1000 labels, ink ribbon = 50 m


THERMOMARK ROLLMASTER 600 - Thermal transfer printer

0804663

https://www.phoenixcontact.com/us/products/0804663



Thermal transfer printer for material off the roll, incl. Euro/US power cable and USB cable. Support CD includes user manuals in several languages, links to firmware, drivers, and planning and marking software. Operating instructions printed in German and English. 1 roll of labels EML (20x8)R white = 1000 labels, ink ribbon = 50 m



https://www.phoenixcontact.com/us/products/1090079



THERMOMARK ROLL 2.0 - Thermal transfer printer

1085260

https://www.phoenixcontact.com/us/products/1085260



Thermal transfer printer for material off the roll, incl. Euro/US power cable and USB cable. Operating instructions printed in German and English. 1 roll of labels EML (20x8)R white = 1000 labels, ink ribbon = 50 m


THERMOMARK ROLL - Thermal transfer printer

5146477

https://www.phoenixcontact.com/us/products/5146477



Thermal transfer printer, 300 dpi, incl. European power cable, US power cable, and USB cable. DVD with CLIP PROJECT advanced planning and marking software, user manuals in various languages, Windows[®] printer driver, and firmware. German/English user manual in DIN A5 format, EML (20x8)R roll of labels, white, with 1000 labels, and ink ribbon: 50 m



https://www.phoenixcontact.com/us/products/1090079



THERMOMARK X1.2 - Thermal transfer printer

5146231

https://www.phoenixcontact.com/us/products/5146231



Thermal transfer printer, weight: 10 kg, length: 0.446 m, width: 242 mm, height: 274 mm, color: gray

THERMOMARK-RIBBON 110 - Ink ribbon

5145384

https://www.phoenixcontact.com/us/products/5145384



Ink ribbon, for roll printers for printing the product groups TML..., WML..., WML HF..., WML-FLAG..., EML.., EML-ESD..., EML-RM..., EML-HA..., EMLS..., EMLC..., EMLP... and PMM..., length: 300 m, roll length: 300 m, width: 110 mm, color: black

1090079

https://www.phoenixcontact.com/us/products/1090079



THERMOMARK-RIBBON 110/50 - Ink ribbon

0800687

https://www.phoenixcontact.com/us/products/0800687



Ink ribbon, for roll printers for printing the product groups TML..., WML..., WML HF..., WML-FLAG..., EML., EML-ESD..., EML-RM..., EML-HA..., EMLS..., EMLC..., EMLP... and PMM..., length: 50 m, roll length: 50 m, width: 110 mm, color: black


THERMOMARK ROLL-ERH - Media hub

5146448

https://www.phoenixcontact.com/us/products/5146448



External media hub, for the THERMOMARK ROLL, for roll diameter of 150 to 400 \mbox{mm}



https://www.phoenixcontact.com/us/products/1090079



THERMOMARK E.300 US - Thermal transfer printer

1287021

https://www.phoenixcontact.com/us/products/1287021



Thermal transfer printer for printing all materials in roll format with a print resolution of 300 dpi. Suitable for long-term use in production and for large print volumes, as large rolls can also be processed.


THERMOMARK E.600 US - Thermal transfer printer

1287029

https://www.phoenixcontact.com/us/products/1287029



Thermal transfer printer for printing all materials in roll format with a print resolution of 600 dpi. Suitable for long-term use in production and for large print volumes, as large rolls can also be processed.



https://www.phoenixcontact.com/us/products/1090079



THERMOMARK E.300 D US - Thermal transfer printer

1287033

https://www.phoenixcontact.com/us/products/1287033



Thermal transfer printer with internal rewinder for printing all materials in roll format with a print resolution of 300 dpi. Suitable for long-term use in production and for large print volumes, as large rolls can also be processed.

THERMOMARK E.600 D US - Thermal transfer printer

1287040

https://www.phoenixcontact.com/us/products/1287040



Thermal transfer printer with internal rewinder for printing all materials in roll format with a print resolution of 600 dpi. Suitable for long-term use in production and for large print volumes, as large rolls can also be processed.

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com