

5x25mm/ No. 241



Indicator, 250V

Time-Current Characteristic
Medium Time Lag (M)

Standard
None

Approvals
None

Specifications

Packaging

002: Pack (100 pcs.)

Materials

Tube: Ceramic
End Caps: Nickel-plated brass

Operating Temperature

-25°C to +70°C (consider de-rating)

Climatic Category

-25°C/+70°C/21 days (EN 60068-1..3)

Stock Conditions

+10°C to +60°C
relative humidity ≤ 75% yearly average,
without dew


Vibration Resistance

24 cycles at 15 min. each (EN 60068-2-6)
10 - 60Hz at 0.75mm amplitude
60 - 2000Hz at 10g acceleration

Marking

Ⓜ, M, Current Rating, 250V

Dimensions (mm)



Limits for Pre-arcing Time

Rated Current	$1.5 \times I_{Rated}$	$2.1 \times I_{Rated}$	$2.75 \times I_{Rated}$	$4 \times I_{Rated}$	$10 \times I_{Rated}$
80mA ... 100mA		<2min		40ms ... 500ms	5ms ... 70ms
125mA ... 1.25A	>1h	<2min	-	60ms ... 2s	5ms ... 70ms
1.6A ... 10A		<30min		60ms ... 2s	5ms ... 70ms

Permissible continuous operating current $I_n \leq 80\%$ at ambient temperature of 25°C (23°C)

Rated Current	Amp Code ²	Voltage Rating	Breaking Capacity	Voltage Drop $1.0 \times I_{Rated}$ max. (mV) Ⓜ	Power Dissipation $1.5 \times I_{Rated}$ max. (W) Ⓜ	Melting Integral $10 \times I_{Rated}$ min. (A ² s) Ⓜ	color of indicator
80mA	0080	250V		520		0.015	grey
100mA	0100	250V		500		0.030	red
125mA	0125	250V	80A @ 250 V AC 50Hz cos φ = 1.0	500		0.053	velvet
160mA	0160	250V		400		0.11	orange
200mA	0200	250V		400		0.23	blue
250mA	0250	250V		375		0.38	yellow
315mA	0315	250V		410		0.60	black
400mA	0400	250V	280		0.75	brown	
500mA	0500	250V	250		1.5	white	
630mA	0630	250V	220		2.3	green	
800mA ⁴	0800	250V	400		3.0	grey	
1A ₄	1100	250V	350		4.5	red	
1.25A ₄	1125	250V	315		6.8	velvet	
1.6A ₁	1160	250V	480		2.3	orange	
2A ₁	1200	250V	360		4.5	blue	
2.5A ₁	1250	250V	1500A @ 250 V AC 50Hz cos φ = 0.7	300		7.5	yellow
3.15A ₁	1315	250V		250		30	black
4A ₁	1400	250V		180		34	brown
6.3A ₁	1630	250V	160		140	green	
8A _{1 2}	1800	250V	Ⓜ160		170	grey	
10A _{1 2}	2100	250V	Ⓜ150		260	red	


¹ 1.6 ... 10A looks like No. 240 ² not mentioned in the norms ³ operating temperature ≥ 10V ⁴ according to DIN 41576, T.2

Note: 1.00 means the number one with two decimal places. 1,000 means the number one thousand.

Order Information

Qty.	Order-Number	Series	Amp Code	Packaging
		241		

5x25mm/ No. 241



Contact Littelfuse for individual I-t curves