



SS Stainless Steel

Metric table

Dimensions in: millimeters - inches

d ₁	d ₂ Thread	Length l									b	h ₁	h ₂	h ₃
		GP (Steel)			GPX (Stainless steel)									
34 <i>1.34</i>	M 6	10 .39	15 .59	20 .79	25 .98	-	-	-	20 .79	30 1.18	14 .55	18 .71	4 .16	.3 .01
34 <i>1.34</i>	M 8	10 .39	15 .59	20 .79	25 .98	-	-	-	-	-	14 .55	18 .71	4 .16	.3 .01
47 <i>1.85</i>	M 6	10 .39	15 .59	20 .79	25 .98	-	-	-	-	-	17 .67	20 .79	4 .16	.3 .01
47 <i>1.85</i>	M 8	10 .39	15 .59	20 .79	25 .98	30 1.18	35 1.38	40 1.57	-	-	17 .67	20 .79	4 .16	.3 .01

Specification

- Wing body
Nylon plastic
- Glass filled
- Temperature resistant up to 230 °F (110 °C)
- Black, matte finish
- **GP**
Threaded stud
Steel
- Zinc plated
- Molded-in
- **GPX**
Threaded stud
Stainless steel, molded-in
European standard 1.4301 (AISI 304)
- **RoHS compliant**

Information

GP and GPX wing screws offer a comfortable two finger grip and expand the range of clamping applications.

On request

- For certain minimum quantities, custom colors or special studs

How to order (Steel threaded stud) ¹ ² ³ GP-47-M6-20	1	Handle diameter d₁
	2	Thread d₂
	3	Length l
How to order (Stainless steel threaded stud) ¹ ² ³ GPX-34-M6-30	1	Handle diameter d₁
	2	Thread d₂
	3	Length l