



JKL LAMP PART NO. (REFERENCE)	COLOR LCD HIGH OUTPUT WHITE 6700°k RGB	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF26409-31B	x = 0.310 y = 0.321	1540	730	5 ± 1	36,000 ± 15%	20,000 MIN. 40,000 AVG.

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

<p>THIRD ANGLE PROJECTION</p>	<p>METRIC</p> <p>DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCE UNLESS OTHERWISE SPECIFIED</p> <p>1 PL +/- 0</p> <p>2 PL +/- 0</p> <p>ANGLE +/- 0</p>	<p>JKL COMPONENTS CORPORATION</p>					
	<p>DRAWN BY L. WENGSTROM</p> <p>APPVD BY LARRY R.</p> <p>DATE 8/14/06</p>	<p>SIZE A</p> <p>SCALE NONE</p>	<p>FSCM NO. 55335</p>	<p>DRAWING NO. BF26409-31B</p>	<p>TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP</p>		
<p>RELEASE AND CANCEL P-0606-05</p>	<p>8/14/06</p>	<p>- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED</p>		<p>RELEASED DATE 8/14/06</p>	<p>REVISION DATE</p>	<p>REV. NO.</p>	<p>SHEET 1 OF 1</p>

REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE