# Product data sheet Characteristics

## ZCMD29

Limit switch body, Limit switches XC Standard, ZCMD, 2NC, silver, snap action





#### Main

Series name Standard format  Product or Component Type  Device short name ZCMD  Design Miniature  Body type Plug-in body  Associated head ZCE06	Range of Product	Telemecanique Limit switches XC Standard
Type         ZCMD           Design         Miniature           Body type         Plug-in body           Associated head         ZCE06	Series name	Standard format
Design   Miniature		Limit switch body
Body type	Device short name	ZCMD
Associated head  ZCE06	Design	Miniature
ZCE66	Body type	Plug-in body
Number of poles 2  Contacts type and composition 2 NC	Associated head	ZCE66 ZCE02 ZCE09 ZCEF0 ZCE62 ZCEH0 ZCE01 ZCE13 ZCE29 ZCEF2 ZCE14 ZCE28 ZCE11 ZCE63 ZCE27 ZCE67 ZCE27 ZCE67 ZCE21 ZCE08 ZCE01 ZCE08 ZCE01 ZCE08 ZCE01 ZCE05 ZCE10 ZCE07 ZCE24 ZCE05 ZCE24
Contacts type and 2 NC composition	Body Material	Zamak
composition	Number of poles	2
Contact operation Snap action		2 NC
	Contact operation	Snap action

#### Complementary

Product Compatibility	XCMD
Associated connection component	ZCMC29L5
	ZCMC29L3
	ZCMC29L7
	ZCMC29L10
	ZCMC29L2
	ZCMC29L1
Electrical connection	Plug-in without pre-cabled connection
Contacts insulation form	Zb
Contacts material	Silver plated contacts
Positive opening	With
Minimum actuation speed	0.01 m/min
Contact code designation	B300, AC-15 (Ue = 240 V), le = 1.5 A EN/IEC 60947-5-1 appendix A
	R300, DC-13 (Ue = 250 V), Ie = 0.1 A EN/IEC 60947-5-1 appendix A

Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Environment	
Depth	0.63 in (16 mm)
Height	1.97 in (50 mm)
Width	1.18 in (30 mm)
Electrical durability	5000000 Cycles, DC-13 120 V, 1 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 24 V, 3 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 2 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C
Short-circuit protection	6 A cartridge fuse gG
[Uimp] rated impulse withstand voltage	4 KV IEC 60664 4 kV IEC 60947-1
Maximum resistance across terminals	25 mOhm IEC 60255-7 category 3
[Ui] rated insulation voltage	300 V 3)UL 508 400 V 3)IEC 60947-5-1 300 V 3)CSA C22.2 No 14

Crucing and shipping details	
Category	22413 - LIMIT SWITCH, IEC, MINIATURE
Discount Schedule	Т
GTIN	3389110299076
Nbr. of units in pkg.	1
Package weight(Lbs)	0.1 lb(US) (0.05 kg)
Returnability	No
Country of origin	ID

## Packing Units

Package 1 Height	0.160 dm	
Package 1 width	0.520 dm	
Package 1 Length	0.310 dm	

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	<sup>™</sup> REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EEU RoHS  Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

### Contractual warranty

	,
Warranty	18 months