1-2273122-1 - ACTIVE

TE Internal #: 1-2273122-1 M12 Cable Assembly, 5 Position, .3 m, Sensor/Actuator, Code A, M12 Plug, M12 Socket, Double Ended, Plastic View on TE.com >



Cable Assemblies > Copper Cable Assemblies > M8/M12 Cable Assemblies > M12 MR-FS Double End Cable Assembly BL



M8/M12 Application Type: Sensor/Actuator

Number of Positions: 5

Connector & Keying Code: A

Connector Type (End A): M12 Plug

Connector Type (End B): M12 Socket

All M12 MR-FS Double End Cable Assembly BL (15)

Features

Product Type Features

Connector Type (End A)

Connector Type (End B)

M12 Plug

M12 Socket

Cable Assembly Type	M12
Configuration Features	
Configuration Number	AA
Number of Positions	5
Electrical Characteristics	
Operating Voltage	125 VAC
Body Features	
Cable Color	Black
Connector Color (End B)	Black
Connector Color (End A)	Black
Jacket Material	PVC
Wire Color (Base)	Brown, White, Blue, Black, Gray
Connector & Keying Code	A
Contact Features	
Contact Current Rating (Max)	4 A

1-2273122-1

M12 Cable Assembly, 5 Position, .3 m, Sensor/Actuator, Code A, M12 Plug, M12 Socket, Double Ended, Plastic



Mechanical Attachment

Thread Size	M12 x M12
Connector Orientation (End A)	Right Angle
Connector Orientation (End B)	Straight
Housing Features	
Housing Material	Plastic
Dimensions	
Outside Cable Diameter	5.2 mm[.204 in]
Wire Size	.326 mm ²
Usage Conditions	
Operating Temperature Range	-30 – 80 °C[-22 – 176 °F]
Operation/Application	
M8/M12 Application Type	Sensor/Actuator
Shielded	No
Packaging Features	
Packaging Quantity	25
Packaging Method	Box

r dekagnig method

Other

Field Serviceable	Yes
Cable Assembly Length	.3 m
Cable Assembly Configuration	Double Ended

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.

C For support call+1 800 522 6752

1-2273122-1

M12 Cable Assembly, 5 Position, .3 m, Sensor/Actuator, Code A, M12 Plug, M12 Socket, Double Ended, Plastic



Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



Customers Also Bought





Documents

Product Drawings M12 angled plug to M12 strgt socket AA

C For support call+1 800 522 6752

1-2273122-1

M12 Cable Assembly, 5 Position, .3 m, Sensor/Actuator, Code A, M12 Plug, M12 Socket, Double Ended, Plastic



English CAD Files 3D PDF 3D Customer View Model ENG_CVM_CVM_1-2273122-1_A.2d_dxf.zip English Customer View Model ENG_CVM_CVM_1-2273122-1_A.3d_igs.zip English Customer View Model ENG_CVM_CVM_1-2273122-1_A.3d_igs.zip English Customer View Model ENG_CVM_CVM_1-2273122-1_A.3d_istp.zip

M8 / M12 Connector System Catalog

English

M8 / M12 Connector System Catalog

Japanese

Product Specifications Product Specification

English