

CA-17P1N12AD00 - Device connector front mounting



1621745

<https://www.phoenixcontact.com/us/products/1621745>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Device connector front mounting, series: RC, angled rotatable, shielded: yes, for standard and SPEEDCON interlock, No. of pos.: 17, Direction of rotation: Standard, contact connection type: Pin, Solder connection, Axial O-ring, 4x Ø 3.2, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1244477

Your advantages

- Easy connection, thanks to infinitely adjustable cable outlet direction up to 310°
- Safe use in the field, thanks to high degree of protection
- Connector for flexible on-site assembly
- Consistent EMC protection for reliable transmission of signals
- Solder connection: proven connection technology for various litz wires

Commercial data

Item number	1621745
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	AB33
Product key	ABRAEM
Catalog page	Page 104 (C-2-2019)
GTIN	4055626001203
Weight per piece (including packing)	129.1 g
Weight per piece (excluding packing)	129.1 g
Customs tariff number	85366990
Country of origin	DE

1621745

<https://www.phoenixcontact.com/us/products/1621745>

Technical data

Product properties

Product type	Circular connectors (device side)
--------------	-----------------------------------

Connector

Insulating body

Coding	N
Insulation body material	PBT
Contact material	CuZn
Contact surface material	Ni/Au
Insertion/withdrawal cycles	100
Connection method	Solder connection
Contact switching type	Pin
Application	Signal
Number of positions	17
Direction of rotation	Standard
Connection profile	17
Rated voltage	48 V AC
	74 V DC
Rated surge voltage	1.5 kV
Overvoltage category	III
Degree of pollution	3
Contact diameter Signal contacts	1 mm
Litz wire cross-section Signal contacts max.	1 mm ²
Nominal current per signal contact	8 A

Housing

Housing material	Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Type of locking	for standard and SPEEDCON interlock
Pg screw connection	none
Degree of protection (plugged in)	IP67
Thread type	M23

CA-17P1N12AD00 - Device connector front mounting




1621745

<https://www.phoenixcontact.com/us/products/1621745>

Drawings

Schematic diagram



CA-17P1N12AD00 - Device connector front mounting





1621745

<https://www.phoenixcontact.com/us/products/1621745>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1621745>

 cUL Recognized Approval ID: E335019-20141210				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	48 V	5 A	- 18	-

 UL Recognized Approval ID: E335019-20141210				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	48 V	8 A	- 18	-

cULus Recognized

1621745

<https://www.phoenixcontact.com/us/products/1621745>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 8.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121100
-------------	----------

1621745

<https://www.phoenixcontact.com/us/products/1621745>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

CA-17P1N12AD00 - Device connector front mounting



1621745

<https://www.phoenixcontact.com/us/products/1621745>

Accessories

SF-Z0019 - Protective cap

1607449

<https://www.phoenixcontact.com/us/products/1607449>



Plastic protection cap, with eye, IP40 for connectors with M23 external thread, RF, SF series

RC-Z2059 - Protective cap

1604225

<https://www.phoenixcontact.com/us/products/1604225>



Plastic protection cap for connectors with M23 external thread

CA-17P1N12AD00 - Device connector front mounting



1621745

<https://www.phoenixcontact.com/us/products/1621745>

RC-Z2469 - Protective cap

1611797

<https://www.phoenixcontact.com/us/products/1611797>



Plastic protection cap, antistatic, for RF, SF, CA, RC series connectors, with M23 external thread

RC-Z2104 - Metal protective cap

1604260

<https://www.phoenixcontact.com/us/products/1604260>



Metal protective cap, M23, degree of protection: IP67, series: RC, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1241739

CA-17P1N12AD00 - Device connector front mounting



1621745

<https://www.phoenixcontact.com/us/products/1621745>

RF-Z0017 - Color-coding

1620624

<https://www.phoenixcontact.com/us/products/1620624>

Color-coding, color: green



RF-Z0018 - Color-coding

1620625

<https://www.phoenixcontact.com/us/products/1620625>

Color-coding, color: orange



CA-17P1N12AD00 - Device connector front mounting



1621745

<https://www.phoenixcontact.com/us/products/1621745>

RF-Z0019 - Color-coding

1620626

<https://www.phoenixcontact.com/us/products/1620626>

Color-coding, color: anthracite



Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com