



16 Hex

.512 (13.0) Dia.

.512 (13.0) Dia.

.476 (12.1)

Recommended Mounting Hole

.110 (2.8)

1/2-28UNEF-2A

.433 (11.0)

.748 (19.0)

1.280 (32.5) Ref.

.610 (15.5) Dia.

.630 (16.0) Dia.

- NOTES: Finish (Plating Thickness in Micro-inches)
1. Brass
  2. Nickel Pl. 100 Min. Thick over Copper Pl. 50 Min. Thick
  3. Phosphor Bronze
  4. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
  5. DELRIN

RoHS Compliant

7	Hex Nut	Note 1	Note 2	1	Dimensions are in Inches Unless Otherwise Specified Tolerances 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4	Part No.	<h1 style="text-align: center;">NTE Electronics</h1>		
7	Lock Washer	Note 1	Note 2	1					
6	Housing	Note 1	Note 2	1					
5	Body	Note 1	Note 2	1					
4	Insulator	Note 5	Natural	1					
3	Contact Pin	Note 3	Note 4	2					
2	Insulator	Note 5	Natural	1					
1	Body	Note 1	Note 2	1	Approved <span style="float: right;">Date 7-7-2010</span> Checked <span style="float: right;">Date 7-7-2010</span> Drawn <span style="float: right;">Date 7-7-2010</span>	Title <span style="float: right;">BNC Female to Female Bulkhead Isolated Adapter</span>			
No	Description	Material	Finish	Q'ty		Drawing No.	Scale 2.5/1	Issue A	Drawing No. <span style="float: right;">06-B014</span>
									File No.