

Specification Sheet

Part Number: 166-90288

Material is easy to use and cut; reduces installation time and labor costs. Flexible, abrasion resistant and durable for a variety of applications.

Good impact strength; recovers quickly if crushed.

UV resistant; suitable for use in outdoor applications.

Offered in fine or coarse corrugated pitch.



HelaGuard Non-Metallic Conduit, Std. Weight, 0.31" Dia., Fine Pitch, PA6, Black, 164 ft/reel

Article Number 166-90288

Type HG-SW0310

Color Black (BK)

Quantity Per reel

Product Description A standard weight corrugated conduit made of PA6 nylon that offers

flexible abrasion protection for wire and cable bundles. Easy to cut and use, the material is highly resistant to solvents and oils. Combine with HelaGuard non-metallic fittings for IP66 rating or greater protection

against water, wind and dirt.

Short Description HelaGuard Non-Metallic Conduit, Std. Weight, 0.31" Dia., Fine Pitch,

PA6, Black, 164 ft/reel

OL-11	D	N.I
Global	Part	ivame

HG-SW0310-PA6-BK

Length L (Imperial)

164.0

Length L (Metric)

50.0

Inner Diameter D (Imperial)

0.39

Inner Diameter D (Metric)

9.8

Outside Diameter OD (Imperial)

0.51

Outside Diameter OD (Metric)

13.0

Nominal Diameter (Imperial)

0.31

Nominal Diameter (Metric)

13

Material

Polyamide 6 (PA6)

Material Shortcut

PA6

Flammability

UL 94 V-2

Halogen Free

Yes

UV Resistant (Yes/No)

No

Operating Temperature

-40°F to +248°F (-40°C to +120°C)

Reach Compliant (Article 33)	No
ROHS Compliant	Yes
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	164.04
Package Quantity (Metric)	50.0
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions