



General ordering data

| | |
|------------------|---|
| Order No. | 1793830000 |
| Part designation | SC 3.81/6/180F3.2SN GN |
| Version | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 6, 180°, Box |
| EAN | 4032248230952 |
| Qty. | 50 pc(s). |

System parameters

| | |
|---|------------------------|
| Fitted to PCB | Soldered connection |
| Outgoing elbow | 180° |
| Pitch | 3.81 mm |
| Pitch in inch | 0.15 inch |
| No. of poles | 6 |
| Solder pin length | 3.2 mm |
| Can be coded | Yes |
| No. of rows | 1 |
| No. of solder pins per pole | 1 |
| Dia. of fitting hole | 1.2 mm |
| Fitting hole tolerance | + 0.1 mm |
| L1 in mm | 19.05 mm |
| L1 in inch | 0.75 inch |
| Insulation resistance | 1,000 MΩ |
| Electric shock protection to DIN VDE 0470 | IP 20 |
| Electric shock protection to DIN VDE 0470 | Safe from finger touch |

Material data

| | |
|---------------------------|---------------------|
| Insulating material | PA GF |
| Colour | Pale green |
| colour chart | Similar to RAL 6021 |
| Insulating material group | II |
| Flammability class UL 94 | V-0 |
| CTI | >= 475 |
| Contact base material | Copper alloy |

Material data

| | |
|---------------------------------------|--------|
| Contact surface | tinned |
| Constant operating temp., min. | -25 °C |
| Constant operating temp., max. | 120 °C |
| Storage temperature, min. | -25 °C |
| Storage temperature, max. | 55 °C |
| Max. relative humidity during storage | 93 % |

DIN IEC rating data

| | |
|--|------------------|
| Rated current, min. No. pins (Tu=20°C) | 17.5 A |
| Rated current, min. No. pins(Tu=40°C) | 17.5 A |
| Rated voltage for overvoltage class/pollution severity III/3 | 160 V |
| Rated impulse withstand voltage for overvoltage class/pollution severity III/3 | 2.5 kV |
| Rated voltage for overvoltage class/pollution severity III/2 | 160 V |
| Rated impulse withstand voltage for overvoltage class/pollution severity III/2 | 2.5 kV |
| Rated voltage for overvoltage class/pollution severity II/2 | 320 V |
| Rated impulse withstand voltage for overvoltage class/pollution severity II/2 | 2.5 kV |
| Short-time withstand current resistance | 3 x 1s with 76 A |

CSA rating data

| | |
|-----------------------------|-------|
| Rated voltage (Use group D) | 300 V |
| Rated current (Use group D) | 10 A |

UL 1059 rating data

| | |
|-----------------------------|-------|
| Rated voltage (Use group D) | 300 V |
| Rated current (Use group D) | 10 A |

Approvals

Approvals institutes



Classifications

| | |
|----------|----------|
| ETIM 2.0 | NK |
| ETIM 3.0 | EC001284 |

Classifications

| | |
|------------|-------------|
| eClass 4.1 | 27-26-07-01 |
| eClass 5.0 | 27-26-07-01 |
| eClass 5.1 | 27-26-07-04 |

Similar products

| Order No. | Part designation | Version |
|------------|------------------------|---|
| 1943180000 | SC 3.81/2/180F3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 2, 180°, Box |
| 1793700000 | SC 3.81/2/180F3.2SN SW | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 2, 180°, Box |
| 1793790000 | SC 3.81/2/180F3.2SN GN | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 2, 180°, Box |
| 1943190000 | SC 3.81/3/180F3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 3, 180°, Box |
| 1793710000 | SC 3.81/3/180F3.2SN SW | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 3, 180°, Box |
| 1793800000 | SC 3.81/3/180F3.2SN GN | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 3, 180°, Box |
| 1943200000 | SC 3.81/4/180F3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 4, 180°, Box |
| 1793720000 | SC 3.81/4/180F3.2SN SW | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 4, 180°, Box |
| 1793810000 | SC 3.81/4/180F3.2SN GN | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 4, 180°, Box |
| 1943210000 | SC 3.81/5/180F3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 5, 180°, Box |
| 1793730000 | SC 3.81/5/180F3.2SN SW | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 5, 180°, Box |
| 1793820000 | SC 3.81/5/180F3.2SN GN | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 5, 180°, Box |
| 1943220000 | SC 3.81/6/180F3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 6, 180°, Box |
| 1793740000 | SC 3.81/6/180F3.2SN SW | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 6, 180°, Box |
| 1943230000 | SC 3.81/7/180F3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 7, 180°, Box |
| 1837010000 | SC 3.81/7/180F3.2SN SW | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 7, 180°, Box |
| 1943370000 | SC 3.81/7/180F3.2SN GN | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 7, 180°, Box |
| 1943240000 | SC 3.81/8/180F3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 8, 180°, Box |
| 1793750000 | SC 3.81/8/180F3.2SN SW | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 8, 180°, Box |
| 1793840000 | SC 3.81/8/180F3.2SN GN | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 8, 180°, Box |
| 1943250000 | SC 3.81/9/180F3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 9, 180°, Box |

| | | |
|------------|-------------------------|--|
| 1943470000 | SC 3.81/9/180F3.2SN SW | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 9, 180°, Box |
| 1943380000 | SC 3.81/9/180F3.2SN GN | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 9, 180°, Box |
| 1943260000 | SC 3.81/10/180F3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 10, 180°, Box |
| 1793760000 | SC 3.81/10/180F3.2SN SW | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 10, 180°, Box |
| 1793850000 | SC 3.81/10/180F3.2SN GN | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 10, 180°, Box |
| 1943270000 | SC 3.81/11/180F3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 11, 180°, Box |
| 1943480000 | SC 3.81/11/180F3.2SN SW | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 11, 180°, Box |
| 1943390000 | SC 3.81/11/180F3.2SN GN | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 11, 180°, Box |
| 1943280000 | SC 3.81/12/180F3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 12, 180°, Box |
| 1793770000 | SC 3.81/12/180F3.2SN SW | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 12, 180°, Box |
| 1793860000 | SC 3.81/12/180F3.2SN GN | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 12, 180°, Box |
| 1943290000 | SC 3.81/13/180F3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 13, 180°, Box |
| 1943490000 | SC 3.81/13/180F3.2SN SW | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 13, 180°, Box |
| 1943400000 | SC 3.81/13/180F3.2SN GN | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 13, 180°, Box |
| 1943300000 | SC 3.81/14/180F3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 14, 180°, Box |
| 1943500000 | SC 3.81/14/180F3.2SN SW | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 14, 180°, Box |
| 1943410000 | SC 3.81/14/180F3.2SN GN | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 14, 180°, Box |
| 1943310000 | SC 3.81/15/180F3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 15, 180°, Box |
| 1943510000 | SC 3.81/15/180F3.2SN SW | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 15, 180°, Box |
| 1943420000 | SC 3.81/15/180F3.2SN GN | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 15, 180°, Box |
| 1943320000 | SC 3.81/16/180F3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 16, 180°, Box |
| 1793780000 | SC 3.81/16/180F3.2SN SW | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 16, 180°, Box |
| 1793870000 | SC 3.81/16/180F3.2SN GN | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 16, 180°, Box |
| 1943330000 | SC 3.81/17/180F3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 17, 180°, Box |
| 1943520000 | SC 3.81/17/180F3.2SN SW | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 17, 180°, Box |
| 1943430000 | SC 3.81/17/180F3.2SN GN | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 17, 180°, Box |

| | | |
|------------|-------------------------|--|
| 1943340000 | SC 3.81/18/180F3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 18, 180°, Box |
| 1943530000 | SC 3.81/18/180F3.2SN SW | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 18, 180°, Box |
| 1943440000 | SC 3.81/18/180F3.2SN GN | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 18, 180°, Box |
| 1943350000 | SC 3.81/19/180F3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 19, 180°, Box |
| 1943540000 | SC 3.81/19/180F3.2SN SW | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 19, 180°, Box |
| 1943450000 | SC 3.81/19/180F3.2SN GN | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 19, 180°, Box |
| 1943360000 | SC 3.81/20/180F3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 20, 180°, Box |
| 1943550000 | SC 3.81/20/180F3.2SN SW | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 20, 180°, Box |
| 1943460000 | SC 3.81/20/180F3.2SN GN | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 20, 180°, Box |