

Notes:

1. Electrical:
   - Meets EIA/TIA-568-B.2-10 Cat.6A Channel Specification
   - Connector Operating Temperature: -40~C to +85~C
2. Materials and Finish:
   - Coupling Ring: Polyester (Black) or Metallized ABS (Nickel Plated); UL94 V-0
   - Plug Housing: Polyester (Black) or Metallized ABS (Nickel Plated); UL94 V-0
   - Interfacial Seal: Silicon, Color: White
   - Cable Gland: PA (Black) or Brass, Nickel Plated
   - Cable Gland Seal: NBR, Color: Black
   - Cable Gland Insert (Metal Version): Nylon, Color: White
   - Cat.6A RJ45 Plug Metal Shell: Copper Alloy, Nickel Plated
   - Cat.6A RJ45 Plug Plastic Housing: Clear Polycarbonate UL94 V-2
   - Cat.6A RJ45 Plug Contacts: Phosphor Bronze, Finish: 50u" Gold min. over Nickel
   - Cable: Cat.6A SSTP, 4 Pairs, AWG26, Stranded, Jacket Color: Black
3. RoHS compliant

Directive 2002/95/EC RoHS Compliant

Cable Length L	Plastic Version	Metallized Plastic Version
2 m	17-150604	17-150634
4 m	17-150614	17-150644
5 m	17-150624	17-150654

Note: Special cable length are available, please contact factory

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION

DO NOT ALTER CAD DRAWING BY HAND

Customer:

Name	Title	Approval Date

Rev.	Changes	Date	Name
a	original		

Tolerance
Unless otherwise specified
0 PLC ±0.50
1 PLC ±0.38
2 PLC ±0.25
3 PLC ±0.10
ANGES ±3°

Autodesk Inventor

	Date	Name
2011		
Draw.	Sept. 22	Vincent Ke
Appd.	Sept. 22	J. Chaudry
Norm		
D-old		

CONEC®

Scale: | Dim. in meter

Material: See Notes

Cat.6A RJ45 Ethernet Patch Cords
Strain Relief to Strain Relief

Drawing No.: 17k1A276 | DIN A3

Part No.: SEE PART NUMBER TABLE | Sheet 1/1