ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00261	Connector, dc plug, 5.5x2.1xL20.5mm, brass nickel plated	1	
2	50-00152	Connector, dc jack, 5.5x2.1xH6.5xL19.5 mm, molding style	1	
3	30-00690	Wire, 2C TS, 22 AWG, UL2464, 300V, 80C, 4.30 mm, VW-1, PVC, white	1	
4	24-00161	Overmold, dc plug, twistlock, PVC	1	white
5	24-00162	Overmold, dc jack, twistlock, PVC	1	white







Notes:
Plug mates with cable assembly: 10-02935 & 10-02979
Jack mates with cable assembly: 10-02934
Functionally equivalent components may be substituted

Wiring Diagram		
50-00261	wire color	50-00152
center	red	center
sleeve	black	sleeve

Revision:	Date:	Description:
A	11/7/2019	Initial release

Prepared: AW Digitally signed by AW Date: 2019.11.07 16:00:24 -08'00'

Verified: PS Digitally signed by PS Date: 2019.11.07 16:01:37 -08'00'

Dimensions are in millimeters.
Tolerances:
X: ± 0.5 mm
X.X: ± 0.3 mm
X.XX: ± 0.05 mm

Notes:
RoHS compliant

Function test: no open, no short circuit, no intermittent

Description:
Cable, 3050 mm, 5.5x2.1mm 50-00261 dc plug twist lock to 5.5x2.1mm 50-00152 dc jack, 22 AWG, white

TENSILITY
tel 1.541.323.3228 800 877.670.7118
fax 1.541.323.4202 web tensility.com

Size: A
Part number: 10-03616
Scale: 1:1
Sheet 1 of 1

To see a custom version of this cable assembly, call Tensility at 541-323-3228 or email engineering@tensility.com

5 4 3 2 1