

# PANDUIT® Stainless Steel Strapping

## Stainless Steel Strapping



### REPLACES TRADITIONAL WING SEAL STRAPS

- Suited to applications requiring higher loop tensile strength and/or wider bearing surfaces than **PAN-STEEL™** ties
- Fast and easy to install using **PANDUIT** installation tool
- Safe to handle—no sharp edges

## STRAPPING Standard Sizes



- Suited to applications requiring higher loop tensile strength and/or wider bearing surfaces than **PAN-STEEL** ties
- Fast and easy to install using **PANDUIT** installation tool.
- Safe to handle—no sharp edges
- Buckle design provides low finished profile—after tensioning, cut end is locked inside buckle
- Standard material is 304 stainless, non-magnetic

\*Nylon coated straps available. Contact factory.

<b>PANDUIT®</b> Part No.	Max. Bundle Dia. In. (mm)	Approx. Length In. (mm)	Approx. Width In. (mm)	Min. Loop Tensile Strength lbs. (n)	Std. Pkg. Qty.	Std. Ctn. Qty.
<b>304 STAINLESS STEEL - .015" THICK</b>						
MS2X375X15-LS	2.00 (50)	10.5 (266)	.375 (10)	300 (1335)	50	250
MS4X375X15-LS	4.00 (102)	16.2 (412)			50	250
MS6X375X15-LS	6.00 (152)	22.5 (572)			50	250
MS8X375X15-LS	8.00 (203)	28.7 (729)			50	250
MS10X375X15-LS	10.00 (254)	35.0 (889)			50	250
MS4X500X15-LS	4.00 (102)	16.2 (412)	.500 (12)	500 (2224)	50	250
MS6X500X15-LS	6.00 (152)	22.5 (572)			50	250
MS8X500X15-LS	8.00 (203)	28.7 (729)			50	250
MS10X500X15-LS	10.00 (254)	35.0 (889)			50	250
MS4X625X15-LS	4.00 (102)	16.2 (412)	.625 (16)	600 (2670)	50	250
MS6X625X15-LS	6.00 (152)	22.5 (572)			50	250
MS8X625X15-LS	8.00 (203)	28.7 (729)			50	250
MS10X625X15-LS	10.00 (254)	35.0 (889)			50	250
<b>304 STAINLESS STEEL - .020" THICK</b>						
MS4X500X20-LS	4.00 (102)	16.2 (412)	.500 (12)	500 (2224)	50	250
MS6X500X20-LS	6.00 (152)	22.5 (572)			50	250
MS8X500X20-LS	8.00 (203)	28.7 (729)			50	250
MS10X500X20-LS	10.00 (254)	35.0 (889)			50	250

## Custom Length Strapping System



- Provides job-site versatility with minimum inventory
- Gives custom capability on larger diameters
- 304 stainless steel
- Buckle is easy to install—just slip onto strapping and turn strapping back on bundle

<b>PANDUIT®</b> Part No.	Thickness In. (mm)	Approx. Width In. (mm)	Used With Buckle	Std. Pkg. Qty.	Std. Ctn. Qty.
<b>STRAPPING</b>					
MS375X15-TSR	.015 (0.4)	.375 (10)	MSB375	200*	—
MS500X15-TSR	.015 (0.4)	.500 (12)	MSB500	200*	—
MS500X20-TSR	.020 (0.5)	.500 (12)	MSB500	200*	—
MS625X15-TSR	.015 (0.4)	.625 (16)	MSB625	200*	—
<b>BUCKLE</b>					
MSB375-CS	Used with .375" width strapping			100	1000
MSB500-CS	Used with .500" width strapping			100	1000
MSB625-CS	Used with .625" width strapping			100	1000

\*Standard Package - TSR = 200 ft. reel. Order the number of reels required. Order the number of bundles required, in multiples of std. pkg. qty.

## INSTALLATION TOOL



BT2MS75

- Replacement nose and gripper provide an economical means to keep tool operating efficiently in the future

<b>PANDUIT®</b> Part No.	Description	Pkg. Qty.
BT2MS75	Tensions, cuts strapping and secures the buckle tab. Used with all widths and thicknesses of <b>PANDUIT</b> strapping	1
BT2N75	Replacement nose section for BT2MS75 tool	1
KT2MG	Replacement tension gripper for BT2MS75 tool	1