ATGBICS FTLX3671DTC36 Finisar Compatible Transceiver DWDM Ch36 SFP+ 1.2 to 11.3GBase (1548.51nm, SMF, 40km, LC, DOM, Ind Temp)

Brand : ATGBICS

Product name : FTLX3671DTC36 Finisar Compatible Transceiver DWDM Ch36 SFP+ 1.2 to 11.3GBase (1548.51nm, SMF, 40km, LC, DOM, Ind Temp)

FTLX3671DTC36 Finisar Compatible Transceiver DWDM Ch36 SFP+ 1.2 to 11.3GBase (1548.51nm, SMF, 40km, LC, DOM, Ind Temp)


ATGBICS FTLX3671DTC36 Finisar Compatible Transceiver DWDM Ch36 SFP+ 1.2 to 11.3GBase (1548.51nm, SMF, 40km, LC, DOM, Ind Temp). SFP transceiver type: Fiber optic, Maximum data transfer rate: 10000 Mbit/s, Interface type: SFP+. Product colour: Silver, Housing material: Metal, Country of origin: United Kingdom. Input voltage: 3.3 V, Maximum voltage: 3.5 V, Power consumption (typical): 1 W. Width: 13.4 mm, Depth: 56.5 mm, Height: 8.5 mm. Number of products included: 1 pc(s), Package type: Box





| Performance | | Power | |
|--|--|--|---|
| Maximum data transfer rate * Interface type * Single-mode fiber (SMF) supported | ximum data transfer rate * 10000 Mbit/s erface type * SFP+ gle-mode fiber (SMF) supported Iti-mode fiber (MMF) supported er optic connector LC P transceiver standard DWDM ximum transfer distance 40000 m evelength 1548.51 nm arse Wavelength Division | Input voltage Maximum voltage Power consumption (typical) | 3.3 V 3.5 V 1 W |
| | | Operational conditions | |
| Multi-mode fiber (MMF) supported Fiber optic connector SFP transceiver standard Maximum transfer distance Wavelength Coarse Wavelength Division Multiplexing (CWDM) | | Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) | -40 °C 85 °C -40 - 85 °C -40 - 85 °C 0 - 95% 0 - 95% |
| Ethernet LAN | 4 | Weight & dimensions | |
| Ethernet interface type Digital Diagnostics Monitoring (DDM) Features | 10 Gigabit Ethernet 🗸 | Width Depth Height Weight | 13.4 mm 56.5 mm 8.5 mm |
| Product colour | Silver | Weight | 19 g |
| Housing materialMetalPlug and PlayImage: Constant of the second secon | Metal ✓ ✓ | Packaging data Number of products included Package type Technical details Sustainability compliance Sustainability continees | 1 pc(s) Box RoHS |
| Brand compatibility Certification | CE, FCC, RoHS | Sustainability certificates Doesn't contain | Lead |

Product code: FTLX3671DTC36-C



5056468764126

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.