	Wiha	Scr	'ew	Hold	ina	Scre	wd	rivers		/iha Sc	row	Hold	ing Scr	<u>'</u> @\\\/	
	vviiic		CVV		ing		wa					TIOIG		ewo	i
0							6.0 × 175 Wbs	a SattFinish ^{an} 397 🧶				-		Lans w	
v		h	2		Clar	nping	slee	ve		(• -	witten jaars maan	SELIONA ST	116		ľ
-	1000000	-				hold			P 🗘			-	Q	-	ĺ
398 SI	otted S	crew-H	loldin	g Scre	wdrive	er, With	n Wiha	a-Square Ha	dle		-				ĺ
Blade C	/M stee	el, hard	ened,	black f	nish.	Clampi	ng sle	eve polyamic	е.		The All Department		A HILLY		
Wiha-squ	lare ha	ndle ce	ellulose	e-aceta	te, imp	act res	sistant	t.	NIEV	N	- 2 -	-		4,8 × 125 Willia	
Item	- ‡ ()	10	—	—	=	==	• •		From Wi	ha					
No.	mm	Inch	mm	Inch	mm	Inch	lbs.	pkg.	FION						
398 25	2.5	.10	75	3.0	160	6.3	.07	10							
398 30	3.0	.12	100	3.9	195	7.6	.11	10	398 92	Set 5 P	cs. Sci	ew Hole	ding Slotte	d & P	1
398 40	4.0	.16	125	5.0	230	9.0	.18	10	Set Bla	de chrome	e-vanad	dium-mo	lybdenum s	steel, h	h
398 50	5.0	.20	150	5.9	265	10.4	.25	10	Wiha so	quare hand	le cellu	lose-ac	etate, impac	ct resis	S
398 60	6.0	.24	175	6.9	290	11.4	.30	10	load cla	mping slee	eve to h	nold scre	ew securely.		
•									Item		10	—		•	
•	-	-					942 × 175 Witha	SattFinish® 397 🔴	No.		mm	mm		Size	e
-				_	01.0		alaa		398 92	398 25	2.5	75	397 00	0	
			1 I	-		nping hold s				398 30	3.0	100	397 01	1	
				and the second se	τn	noia e	screw			398 40	4.0	125			

Wiha Magnetizer/Demagnetizer

290

.30 10

11.4

175

7.0



Application.

Application.											
To magnetiz	o magnetize, lead tool slowly through the (+) opening,										
to demagne	etize guide tool slowly through the (-) opening.										
Item											
No.	Dimensions	lbs.									
400 10	2.1" x 2.0" x 1.1"	.30									

(Parts under 1" Length or 1/8" Diameter may not demagnetize)

PREVIOUS

NEXT



r Sets

Screwdriver ed, black finish. With spring

load blamping blocke to hold below becarely.												
Item		10	 =		0	—	•••					
No.		mm	mm		Size	mm	lbs.					
398 92	398 25	2.5	75	397 00	0	100	.87					
	398 30	3.0	100	397 01	1	125						
	398 40	4.0	125									



398 96 Set 8 Pcs. Screw Holding Slotted & Phillips Screwdriver Set Blade chrome-vanadium-molybdenum steel, hardened, black finish. Wiha square handle cellulose-acetate, impact resistant. With spring load clamping sleeve to hold screw securely.

Item		‡ ()	—	-	•	≕ ■	•••
No.		mm	mm		Size	mm	lbs.
398 96	398 25	2.5	75	397 00	0	100	1.80
	398 30	3.0	100	397 01	1	125	
	398 40	4.0	125	397 02	2	175	
	398 50	5.0	150				
	398 60	6.0	175				



397 02