



_	ı	2	3		4
A	METRAL P/N ROW I 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 D 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	70451-X015LF D 3 3 3 3 3 3 3 3 3 B 3 3 3 3 3 3 3 3 3	MOD. 2 MOD. 3 7	ROW I 2 3 4 5 6 7 8 9 10 11 1 D 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	MOD. 3 12 13 14 15 16 17 18 5 5 5 5 5 5 5 5 6 6 6 6 6 6 6 6 6 6 6 6 6
_	METRAL P/N ROW I 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 OUNTACT CODE MOD. 2 MOD. 3 MOD. 2 MOD. 3 MOD. 3 MOD. 3 MOD. 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	METRAL P/N ROW I 2 3 3 4 5 6 D 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 70451-X02	ROW I 2 3 4 5 6 7 8 9 10 11 1 D 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 1	MOD. 3 12 13 14 15 16 17 18 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5
8 2 2 3	METRAL P/N ROW I 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 D I I I I I I I I I I I I I I I I I I	70451-X017LF	MOD. 2 MOD. 3 7 8 9 10 11 12 13 14 15 16 17 18 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	ROW	MOD. 3 12 13 14 15 16 17 18 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 7 7 7 7
Amphenol FCi	METRAL P/N ROW I 2 S MOD. 2 MOD. 3 D 3 3 3 3 3 3 3 3 3	METRAL P/N ROW I 2 3 4 5 6 6 D 3 3 3 3 3 3 3 3 3 6 7 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	MOD. 2 MOD. 3 7 8 9 10 11 12 13 14 15 16 17 18 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 70451-X02	ROW I 2 3 4 5 6 7 8 9 10 11 1 D 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	MOD. 3 12 13 14 15 16 17 18 7 7 7 7 7 7 7 7 7 6 6 6 6 6 6 6 6 6 6
Corporation	METRAL P/N ROW I 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 D 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	70451-X019LF B 4 4 4 4 4 4 4	MOD. 2 MOD. 3 7 8 9 10 11 12 13 14 15 16 17 18 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	ROW	7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
© 2020 Amphenol	spec ref * dr tolerance std ISO 406 OTHERWISE SPECIFIED app	9 Narayanan, Aru 2021/01/21	projection product family	Size A ecn no METRAL rel leve	scale
•	0.XXX ±0.050	FCi	SIGNAL HEADER ROW PRESS-FIT - Produ 3 PDS: R	S 704	sheet 3 of 9

_	1	2	3		4
А	METRAL P/N ROW I 2 MOD. 2 MOD. 3 D 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	70451-X030LF	MOD. 2 MOD. 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	METRAL P/N ROW I 2 3 4 5 6 6 D II	MOD. 2 MOD. 3 7 8 9 10 11 12 13 14 15 16 17 18 11 11 11 11 11 11 11 11 11 11 11 11 11
	METRAL P/N ROW 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 D 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	70451-X031LF C 9 9 9 9 B 9 9	MOD. 2 MOD. 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	70451-X036LF D 10 10 10 10 10 10 10 10 10 10 10 10 10	MOD. 2 MOD. 3 7 8 9 10 11 12 13 14 15 16 17 18 10 10 10 10 10 10 10 10 10 10 10 10 10 1
Per	METRAL P/N ROW I 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 D 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	70451-X032LF B 9 9 9	4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	170451-X0371F	11 11 11 11 11 11 11 11 11 11 11 11 11
Amphenol FCi	METRAL P/N ROW I 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 D 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	D	MOD. 2 MOD. 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 11 11 11 11 11 11 11 11 11 11 11 11 11	METRAL P/N ROW CONTACT CODE MOD.	9 9 9 9 9 9 9 9 9 9 9 9 9 9
ation	METRAL P/N ROW 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 D 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	METRAL P/N ROW 2 3	MOD. 2 MOD. 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 11 12 12 12 12 12 12 12 12 11 11 11 11	C 2 2 2 2 2 2	MOD. 2 MOD. 3
Amphenol Corporation	TOLERANCES INLESS TOLERANCES INLESS TOLERANCES INLESS TOLERANCES INLESS TOLERANCES INLESS INLESS TOLERANCES INLESS INLE	Terran Huang 2 Narayanan, Aru 2	11 1 1 1 1 1 1 1 1 1	A 12 12 12 12 12 12	12 12 12 12 12 12 12 12
© 2020 /	150 406 150 1101 OTHERWISE SPECIFIED app	nphenol	PRAL SIGNAL HEAD OD., 4 ROW PRESS-FIT		rel level Released 7045 R
	V	henol-icc.com cat. no.	3	Product - Custome	

1	2	3	4
A P/N ROW I 2 3 4 5 6 7 8 9 D 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	MOD. 3 METRAL P/N ROW I 2 3 4 5 5 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	6 7 8 9 10 11 12 13 14 15 16 17 18 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	A
P/M MOU. I	CONTACT CODE MOD. 1 10 11 12 13 14 15 16 17 18 P/N ROW 1 2 3 4 5 5 10 19 19 19 19 19 19 19	6 7 8 9 10 11 12 13 14 15 16 17 18 P/N ROW 19 19 19 19 19 19 19 19 19 19 19 19 19 1	CONTACT CODE MOD. 2 MOD. 3 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6
B 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	A A A A A A A A A A	A MOD. 2 MOD. 3 6 7 8 9 10 11 12 13 14 15 16 17 18 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 D	CONTACT CODE MOD. 2 MOD. 3 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 5 5 5 5 5 5 5 5 5
TO451-X042LF	1	3 3 3 3 3 3 3 3 3 3	S S S S S S S S S S
C TO 451 - XO 43LF B 3 3 3 3 3 3 3 3 3	3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	19	7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
TO451-X044LF D 2 2 2 2 2 2 2 2 2	3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 6 6 6 6 6 7 <th>6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6</th>	6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6
D ISO 406 OTHERWISE	dr Terran Huang 2010/07/0		Size Scale
surface3.200 linear 0	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	L SIGNAL HEADER 4 ROW PRESS-FIT	70451 R
ISO I302 angular	amphenol-icc.com cat. no.	- Product -	Customer Drw sheet 5 of 9 STATUS:Released Printed: Jan 28, 2021

	2	3	4
A S S S S S S S S S S S S S S S S S S S	No. No.	5 6 7 8 9 10 11 12 13 14 15 16 17 18 P/N R(10 10 10 10 10 10 10 10 10 10 10 10 10 1	
METRAL P/N ROW I 2 3 4 5 6 7 8 9 I TO 451-X056LF B 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	11 12 13 14 15 16 17 18 P/N ROW 1 2 3 4 4 5 6 7 7 7 7 7 7 7 7 7	P/N	2 11 11 11 11 11 11 11 11 11 11 11 11 11
D 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	No. 1 12 13 14 15 16 17 18 P/N ROW 1 2 3 4 4 4 14 14 14 14 1	5 6 7 8 9 10 11 12 13 14 15 16 17 18 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	C
C D 20 20 20 20 20 20 20 20 20 20 20 20 20	No. 1 12 13 14 15 16 17 18 P/N Row 1 2 3 4 4 5 16 17 18 P/N Row 1 2 3 4 4 5 16 17 18 P/N Row 1 2 3 4 4 4 1 1 1 1 1 1 1	5 6 7 8 9 10 11 12 13 14 15 16 17 18 15 15 15 15 15 15 15 15 15 15 15 15 15 1	
D 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	METRAL P/N ROW 1 2 3 4 4 5 16 17 18 P/N ROW 1 2 3 4 4 5 16 17 18 P/N ROW 1 2 3 4 4 15 16 17 17 7 7 7 7 7 7 7	METRAL P/N RC	CONTACT CODE MOD. 2 MOD. 3 OW 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 D 12 12 12 12 12 12 12 1
spec ref * tolerance std ISO 406 ISO 1101 O.	S UNLESS e n g Narayanan, Aru 2021.	projection projection projection product family RAL SIGNAL HEADER	MM
Surface 3.200 linear 0.X 0.X 150 1302 angular 0°	$\frac{x}{(x)} = \frac{\pm 0.13}{\pm 0.050}$ FCi $\frac{\pm}{2}$ 3 MOD	, 4 ROW PRESS-FIT	7045 R - Customer Drw sheet 6 of 9

	<u> </u>	2	3	4	
	METRAL P/N ROW CONTACT CODE MOD. 2 MOD. 2	MOD. 3 12 3 4 15 16 17 18 4 4 4 4 4 4 4		METRAL P/N ROW 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	
A	T0451-X070LF C 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	C C C C C C C C C C	3 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	70451-X080LF C 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	
	METRAL P/N ROW 2 3 4 5 6 7 8 9 10 11	MOD. 3 12 3		METRAL P/N ROW 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	
	70451-X071LF	3 3 3 3 3 3 3 3 3 3 3 1 TO 45 I - XO 76 L F B		70451-X081LF C 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	
В	METRAL P/N ROW 2 2 2 2 2 2 2 2 2	MOD. 3 12 13 14 15 16 17 18 P/N RO 2 2 2 2 2 2 2		METRAL P/N ROW 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	
N N	70451-X072LF C 4 4 4 4 4 4 4 4 4 4 4 4 4	4 4 4 4 4 4 4 6 A A A A A A A A A A A A	3 3 <td>70451-X082LF B 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8</td> <td></td>	70451-X082LF B 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	
	METRAL P/N ROW 2 2 2 2 2 2 2 2 2	MOD. 3 12 13 14 15 16 17 18 P/N RO 2 2 2 2 2 2 2		METRAL P/N ROW 2 3 4 5 6 7 8 9 10 11 12 13 4 15 6 6 6 6 6 6 6 6 6	
C	T0451-X073LF C	3 3 3 3 3 3 3 3 C TO451-X078LF B	3 3 <td>T0451-X083LF C 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7</td> <td></td>	T0451-X083LF C 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	
<u>uo</u>	METRAL P/N ROW 2 2 2 2 2 2 2 2 2	MOD. 3 12 3 14 15 16 17 18 P/N RO 2 2 2 2 2 2 2 D		METRAL P/N ROW 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	
	70451-X074LF	3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	3	70451-X084LF C 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	
Amphenoi	spec ref * tolerance std	dr Terran Huang	2010/07/09 projection 2021/01/21	MM size scale	
2020 Am	ISO 406 OTHERWISE SP	UNLESS chr -		e c n n o ELX-1-39704-1	
	surface3.200 linear 0.XX	±0.3 +0.3 Amphenol	METRAL SIGNAL HEADE	ER 2 70451	e v
		±0.030	3 MOD, 4 ROW PRESS-FIT	Product - Customer Drw sheet 7 of 9	R
c	reo File:ELX:#K-AKC,REV F.2020-12-21	2	3	PDS: Rev :R STATUS:Released Printed: Jan 2	

	2	3	4
	6 6 6 6 6 6 6 6 70451-Y0901F C 10 10 10 10 10 10	12 12 12 12 12 12 12 12 12 12 12 12 12 1	CONTACT CODE MOD. 2 MOD. 3 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 10 10 10 10 10 10 10 10 10 10 10 10 10 1
A 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	T T T T T T T T T T	MOD. 2 MOD. 3 METRAL P/N ROW	CONTACT CODE MOD. 2 MOD. 3
B 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	TOUR STANDARD TOUR STANDAR	MOD. 2 MOD. 3 7 8 9 10 11 12 13 14 15 16 17 18 10 10 10 10 10 10 10 10 10 10 10 10 10 1	10 10 10 10 10 10 10 10 10 10 10 10 10 1
	Total	A MOD. 2 MOD. 3 7 8 9 10 11 12 13 14 15 16 17 18 METRAL P/N ROW	1 1 1 1 1 1 1 1 1 1
C T T T T T T T T T	TOURTH T		
TO451-X089LF C 20 20 20 20 20 20 20 20 20 20 20 20 20	20 20 20 20 20 20 20 20		9
spec ref * tolerance std ISO 406 ISO 1101 TOLERANCES OTHERWISE S		projection product family	MM
surface3.200 linear 0.XX 0.XXX	+0.050 FCi + 3 MOD, 4	SIGNAL HEADER ROW PRESS-FIT	70451 R
ISO I302 angular 0°	±2° amphenol-icc.com cat. no.	- Product - 3 PDS: Rev :R	Customer Drw sheet 8 of 9 STATUS:Released Printed: Jan 28, 2021

