Mallory Sonalert Products,Inc. Sales Outline Drawing Revision: CUL Recognized as capable of meeting Medical Sp Sound Level Category: Mode of Operation: Continuous Voltage Rating: 9 to 12 VDC Frequency: 150 to 4000 Hz Loudness @ 10cm: Average Current Draw: Verage Current Draw: Inches (mm) Part #: Revision: Revision: Revision: Revision: Revision: Revision: Revision: Revision: Audits as capable of meeting Medical Sp out a capable of meeti	
Sound Level Category: Mode of Operation: Voltage Rating: 9 to 12 VDC Frequency: 150 to 4000 Hz Loudness @ 10cm: 85 to 95 dB(A) Typ. Average Current Draw: 25mA Typ. Ipk Current*: 75mA Housing Material: Storage Temperature: -40° to +85° C Operating Temperature: -30° to +65° C Weight Typical: Options: Dimensions: Inches (mm) CUL Recognized PATENT NUMBER: 7880593 Before Code Date: 1546 Not cUL Recognized After Code Date: 1546	ROHS Compliant
Sound Level Category: Mode of Operation: Voltage Rating: Prequency: Loudness @ 10cm: Average Current Draw: Ipk Current*: Housing Material: Storage Temperature: Operating Temperature: Weight Typical: Options: Dimensions: Inches (mm) Storage Temperature: Dimensions: Inches (mm) Loud Continuous Oto 12 VDC Frequency: 150 to 4000 Hz 85 to 95 dB(A) Typ. 425mA Typ. ABS 777D Plastic Resin, Bla ABS 777D Plastic Resin, Bla ABS 777D Plastic Resin, Bla Coperating Temperature: -40° to +85° C Operating Temperature: -30° to +65° C Weight Typical: 0.6 oz (17g) Please contact factory. Dimensions: Inches (mm) After Code Da Options: Option	ROHS Compliant
Voltage Rating: Frequency: Loudness @ 10cm: Average Current Draw: Ipk Current*: Housing Material: Storage Temperature: Operating Temperature: Weight Typical: Options: Dimensions: Voltage Rating: 9 to 12 VDC 150 to 4000 Hz 85 to 95 dB(A) Typ. 85 to 95 dB(A) Typ. 225mA Typ. 75mA ABS 777D Plastic Resin, Bla Storage Temperature: -40° to +85° C Operating Temperature: -30° to +65° C Weight Typical: O.6 oz (17g) Options: Please contact factory. Dimensions: Inches (mm) CUL Recognized PATENT NUMBER: 7880593 Before Code Date: 1546 Not cUL Recognized After Code Date: 1546	ROHS Compliant
Frequency: Loudness @ 10cm: Average Current Draw: Page	ROHS Compliant
Loudness @ 10cm: Average Current Draw: John Current*: John Current*:	ROHS Compliant
Average Current Draw: John Current*:	ROHS Compliant
Ipk Current*: 75mA Housing Material: ABS 777D Plastic Resin, Black Storage Temperature: -40° to +85° C Operating Temperature: -30° to +65° C Weight Typical: 0.6 oz (17g) Options: Please contact factory. Dimensions: Inches (mm) CUL Recognized PATENT NUMBER: 7880593 Before Code Date: 1546 Not cUL Recognized After Code Date: 01.750 [044.5]	ROHS Compliant
Housing Material: Storage Temperature: Operating Temperature: Weight Typical: Options: Dimensions: Inches (mm) Patent Number: 7880593 Before Code Date: 1546 Not cUL Recognized ABS 777D Plastic Resin, Black -40° to +85° C -30° to +65° C 0.6 oz (17g) Please contact factory. CUL Recognized PATENT NUMBER: 7880593 After Code Date: 1546 After Code Date: 1546	ROHS Compliant
Storage Temperature: Operating Temperature: Weight Typical: Options: Dimensions: Inches (mm) PATENT NUMBER: 7880593 Before Code Date: 1546 Not cUL Recognized PATENT NUMBER: 780593 After Code Date: 044.5	ROHS Compliant
Operating Temperature: Weight Typical: Options: Dimensions: Inches (mm) PATENT NUMBER: 7880593 Before Code Date: 1546 Not cUL Recognized PATENT NUMBER: 780593 After Code Date: 044.5	•
Weight Typical: Options: Dimensions: Inches (mm) PATENT NUMBER: 7880593 Before Code Date: 1546 Not cUL Recognized After Code Date: 01.750 [Ø44.5]	•
Options: Dimensions: Inches (mm) Please contact factory. CUL Recognized PATENT NUMBER: 7880593 Before Code Date: 1546 Not cUL Recognized After Code Date: 044.5	•
Dimensions: Inches (mm) PATENT NUMBER: 7880593 Before Code Date: 1546 Not cUL Recognized After Code Date: 01.750 [Ø44.5]	•
PATENT NUMBER: 7880593 Before Code Date: 1546 Not cUL Recognized After Code Date: 01.750 [Ø44.5]	•
Before Code Date: 1546 Not cUL Recognized After Code Date: 01.750 [Ø44.5]	ate: 1547 cUL Recognized
Ø0.138 [Ø3.50] 2 places	TRANDED OL WIRES 6 INSULATED (. 6" LONG WIRE (-) IRE (+)

*lpk = Instantaneous Peak

tolerances:

±0.01 [±0.3]

±0.005 [±0.1]