

Computer Power Cord, NEMA 5-15P to Left-Angle C13 - 10A, 125V, 18 AWG, 6 ft. (1.83 m), Black

MODEL NUMBER: P006-006-13LA









Computer power cord with left-angled C13 plug allows connection of a PC, monitor or printer in a tight space or at an awkward angle.

Features

Desktop Computer Power Cord Connects PCs, Printers, Monitors and Other EquipmentThis desktop computer power cord is designed for computers, monitors, scanners, printers and other compatible peripherals. It features a left-angled C13 end for connecting to a device and a 5-15P plug for connecting to an AC power source. The 6-ft. (1.83 m) length allows you some flexibility in placing equipment with respect to the power outlet.

Left-Angle C13 Plug Makes Connecting in Tight Spaces EasierThe angled C13 connector makes installations easier in confined spaces, such as the back of a rack enclosure cabinet. When plugged in, the left-angled plug guides the computer power supply cable parallel to your peripheral, allowing you to push the device up against a wall or hide it behind a desk to maximize space.

Highlights

- Left-angle C13 plug allows easier connection in confined or hard-to-reach spaces
- Recommended for powering computers, printers and other compatible peripherals
- Adds 6-ft. (1.83 m) to your existing power connection to provide flexibility in placing devices
- Ideal replacement for worn-out or missing computer power cord
- NEMA 5-15P plug connects to AC power; C13 plug connects to device's C14 inlet

Applications

- Connect devices like computers, monitors, scanners and printers to a power outlet up to 6-ft. (1.83 m) away in your home office, work space or dorm room
- Extend an existing power connection up to 6-ft. (1.83 m) to more easily place a device or reach a power source away from your workstation
- Provide a high-quality replacement for a worn-out or missing power cord
- Power a device located in a hard-to-access area behind a desk or flush against a wall

Package Includes

 P006-006-13LA NEMA 5-15P to Left-Angle C13 Power Extension Cable, 6-ft. (1.83 m), Black

Specifications

| OVERVIEW | | |
|-----------------------------|---|--|
| UPC Code | 037332156464 | |
| Device Compatibility | Computer; Monitor/HDTV; Printer; Server; UPS; PDU | |
| Country/Region | North America | |
| | | |
| INPUT | | |
| Maximum Input Amps | 10 | |
| Voltage Compatibility (VAC) | 125 | |



| Plug Color Black Cable Jacket Color Black Cable Jacket Material PVC Cable Jacket Material PVC PV | | | |
|--|---------------------------------|-----------------------------|--|
| Gable Jacket Color | PHYSICAL | | |
| Cable Jacket Material PVC Cable Jacket Rating VW-1 Power Cord Jacket Type SJT Cable Outer Diameter (OD) 7.8mm Number of Conductors 3 Wife Gauge (AWG) 18 Wife Gauge (AWG) 18 Wife Gauge (AWG) 18 Wife Gauge (Do - mm²) 0.82 Cable Length (ft.) 6 Cable Length (ft.) 6 Cable Length (m) 1.83 Shipping Dimensions (hwd / rm) 1.000 x 7.10 x 0.50 Shipping Dimensions (hwd / rm) 2.54.04 x 18.03 x 1.27 Shipping Weight (ba) 0.21 ENVIRONMENTAL Operating Temperature Range 4-4* to 140°F (-20° to 60°C) Storage Temperature Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 NEMA 5-15P | Plug Color | Black | |
| Cable Jacket Rating VW-1 Power Cord Jacket Type SJT Cable Outer Diameter (OD) 7.8mm Number of Conductors 3 Wire Gauge (AWG) 18 Wire Gauge (AWG) 0.82 Cable Length (ft.) 6 Cable Length (ft.) 6 Cable Length (fm) 1.83 Shipping Dimensions (hwd / in.) 10.00 x 7.10 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 18.03 x 1.27 Shipping Weight (bs.) 0.51 Shipping Weight (kg) 0.23 ENVIRONMENTAL Operating Temperature Range 4° to 140°F (-20° to 60°C) Storage Temperature Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 EC-320-C13 - LEFT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Cocking Plug School Rating No Cocking Plug School Rating No Cocking Plug No Cocking Plug School Rating No Cocking Plug No Cocking Plu | Cable Jacket Color | Black | |
| Power Cord Jacket Type SJT Cable Outer Diameter (OD) 7.8mm Number of Conductors 3 Wire Gauge (AWG) 18 Wire Gauge (OD - mm²) 0.82 Cable Length (III) 6 Cable Length (III) 18.3 Shipping Dimensions (Itwd / in.) 10.00 x 7.10 x 0.50 Shipping Dimensions (Itwd / cm) 25.40 x 18.03 x 1.27 Shipping Weight (Ibs.) 0.51 Shipping Weight (Ikg) 0.23 ENVIRONMENTAL Operating Temperature Range -4" to 140°F (-20" to 60°C) Operating Temperature Range -4" to 140°F (-20" to 60°C) Operating Humidity Range Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 Side B - Connector 1 IEC-320-C13 - LEFT ANGLE FEATURES & SPECIFICATIONS Antibacterial Antibacterial No Angled Plug Yes High Yottage No Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE | Cable Jacket Material | PVC | |
| Cable Outer Diameter (OD) 7.8mm Number of Conductors 3 Wire Gauge (AWG) 18 Wire Gauge (OD - mm²) 0.82 Cable Length (It) 6 Cable Length (m) 1.83 Shipping Dimensions (twd / in.) 10.00 x 7.10 x 0.50 Shipping Dimensions (twd / cm) 25.40 x 18.03 x 1.27 Shipping Weight (kg) 0.23 ENVIRONMENTAL Operating Temperature Range -4" to 140"F (-20" to 60"C) Storage Temperature Range -4" to 140"F (-20" to 60"C) Operating Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 - LEFT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Coiled Power Cord No | Cable Jacket Rating | VW-1 | |
| Number of Conductors 3 Wire Gauge (AWG) 18 Wire Gauge (OD - mm²) 0.82 Cable Length (It.) 6 Cable Length (m) 1.83 Shipping Dimensions (hwd / in.) 10.00 x 7.10 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 18.03 x 1.27 Shipping Weight (Ibs.) 0.51 Shipping Weight (kg) 0.23 ENVIRONMENTAL Operating Temperature Range -4" to 140"F (-20" to 60"C) Storage Temperature Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 - LEFT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Colled Power Cord No STANDARDS & COMPLIANCE | Power Cord Jacket Type | SJT | |
| Wire Gauge (AWG) 18 Wire Gauge (DD - mm²) 0.82 Cable Length (ft.) 6 Cable Length (m) 1.83 Shipping Dimensions (hwd / in.) 10.00 x 7.10 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 18.03 x 1.27 Shipping Weight (lbs.) 0.51 Shipping Weight (kg) 0.23 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 IEC-320-C13 - LEFT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Colled Power Cord No STANDARDS & COMPLIANCE | Cable Outer Diameter (OD) | 7.8mm | |
| Wire Gauge (OD - mm²) 0.82 Cable Length (ft.) 6 Cable Length (m) 1.83 Shipping Dimensions (hwd / in.) 10.00 x 7.10 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 18.03 x 1.27 Shipping Weight (lbs.) 0.51 Shipping Weight (kg) 0.23 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 - LEFT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE | Number of Conductors | 3 | |
| Cable Length (ft.) 6 Cable Length (m) 1.83 Shipping Dimensions (hwd / in.) 10.00 x 7.10 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 18.03 x 1.27 Shipping Weight (lbs.) 0.51 Shipping Weight (kg) 0.23 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 - LEFT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Colled Power Cord No STANDARDS & COMPLIANCE | Wire Gauge (AWG) | 18 | |
| Cable Length (m) 1.83 Shipping Dimensions (hwd / in.) 10.00 x 7.10 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 18.03 x 1.27 Shipping Weight (lbs.) 0.51 Shipping Weight (kg) 0.23 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-16P Side B - Connector 1 IEC-320-C13 - LEFT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE | Wire Gauge (OD - mm²) | 0.82 | |
| Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) Shipping Weight (kg) 0.23 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 - LEFT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Coiled Power Cord No STANDARDS & COMPLIANCE | Cable Length (ft.) | 6 | |
| Shipping Dimensions (hwd / cm) 25.40 x 18.03 x 1.27 Shipping Weight (kg) 0.51 Shipping Weight (kg) ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 - LEFT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Colled Power Cord No | Cable Length (m) | 1.83 | |
| Shipping Weight (lbs.) Shipping Weight (kg) 0.23 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 - LEFT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Colied Power Cord No STANDARDS & COMPLIANCE | Shipping Dimensions (hwd / in.) | 10.00 x 7.10 x 0.50 | |
| Shipping Weight (kg) ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 - LEFT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Coiled Power Cord No STANDARDS & COMPLIANCE | Shipping Dimensions (hwd / cm) | 25.40 x 18.03 x 1.27 | |
| ENVIRONMENTAL Operating Temperature Range | Shipping Weight (lbs.) | 0.51 | |
| Operating Temperature Range | Shipping Weight (kg) | 0.23 | |
| Storage Temperature Range | ENVIRONMENTAL | | |
| Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 - LEFT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE | Operating Temperature Range | -4° to 140°F (-20° to 60°C) | |
| Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 - LEFT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Coiled Power Cord No | Storage Temperature Range | -4° to 140°F (-20° to 60°C) | |
| Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 - LEFT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE | Operating Humidity Range | 10% to 65% RH | |
| Side A - Connector 1 Side B - Connector 1 IEC-320-C13 - LEFT ANGLE FEATURES & SPECIFICATIONS Antibacterial Angled Plug Yes High Voltage No Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE | Storage Humidity Range | 10% to 65% RH | |
| FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Coiled Power Cord No | CONNECTIONS | | |
| FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE | Side A - Connector 1 | NEMA 5-15P | |
| Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Coiled Power Cord No | Side B - Connector 1 | IEC-320-C13 - LEFT ANGLE | |
| Angled Plug Yes High Voltage No Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE | FEATURES & SPECIFICATIONS | | |
| High Voltage No Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE | Antibacterial | No | |
| Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE | Angled Plug | Yes | |
| Coiled Power Cord No STANDARDS & COMPLIANCE | High Voltage | No | |
| STANDARDS & COMPLIANCE | Locking Plug | No | |
| | Coiled Power Cord | No | |
| | STANDARDS & COMPLIANCE | | |
| Product Certifications cUL Listed; UL Listed | Product Certifications | cUL Listed; UL Listed | |



| Product Compliance | RoHS |
|--|---------------------------|
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.