

Part Number	Contact Area Plating Finish
KMBVXHT-TH2-B	Gold Flash (standard)
KMBVXHT-TH2-B30	30u" Gold (30 option)

Recommended PCB Layout
(Top View)

Material and Finish

Insulator: High Temperature Thermoplastic, UL 94V-0 Rated, Black

Shell: Phosphor Bronze, Nickel Plated

Contact Material: Phosphor Bronze

Contact Plating Options:

Standard: Gold Flash on Contact Area, Tin Plated on Solder Tails, All over Nickel Underplate

30 Option: 30u" Gold Plated on Contact Area, Tin Plated on Solder Tails, All over Nickel Underplate

Electrical Characteristics

Rated Current: 1A

Rated Voltage: 30V AC/DC

Insulation Resistance: 100 Megohms Min.

Contact Resistance: 50 milliohms Max.

Dielectric Withstanding Voltage: 100V AC For 1 Minute

Mechanical Characteristics

Durability: 5000 Mating Cycles Min.

Operating Temperature: -55°C to +85°C

Tolerances

X.X ± 0.35
X.XX ± 0.25
Unless Stated Otherwise




REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A0	05/30/17	New Drawing	J. Elbanna	G. Serrato	J. Elbanna	05/30/17
A1	08/08/17	Release Drawing	G. Serrato	C. Kelleher		

KMBVXHT-TH2-Bxx

USB, Mini-B Type socket

High Temp, Vertical Mount, Through Hole



UNITS
mm