

## Cable lug - C-PCI 1,5/2 - 3240064

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Pin cable lug, red, 0.5 - 1.5 mm<sup>2</sup>, L1=12 mm



### Product Features

- Electrolytic tin plating
- Hard-soldered crimping zone for maximum pull-out forces
- Halogen-free
- 'EASY ENTRY' for easy and reliable conductor entry



### Key commercial data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 PCE    |
| Minimum order quantity               | 100 PCE  |
| Weight per Piece (excluding packing) | 0.8 GRM  |
| Custom tariff number                 | 85369010 |
| Country of origin                    | China    |

### Technical data

#### Dimensions

|  |         |
|--|---------|
| Length (b)                                   | 22.5 mm |
| Length contact range                         | 12 mm   |
| Length of insulation sleeve (c)              | 10.5 mm |
| Inner dimension of the insulating collar (d) | 4.1 mm  |
| Inner diameter (f)                           | 2 mm    |
| Material thickness (g)                       | 0.75 mm |

#### Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -20 °C ... 105 °C |
|---------------------------------|-------------------|

#### General

## Cable lug - C-PCI 1,5/2 - 3240064

### Technical data

#### General

|   |              |
|---|--------------|
| Color                                   | red          |
| Stripping length                        | 7 mm         |
| Components                              | Halogen-free |
| Inflammability class according to UL 94 | V2           |
| Material                                | Copper       |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27060701 |
| eCl@ss 4.1 | 27060701 |
| eCl@ss 5.0 | 27400201 |
| eCl@ss 5.1 | 27400201 |
| eCl@ss 6.0 | 27400201 |
| eCl@ss 7.0 | 27400201 |
| eCl@ss 8.0 | 27400201 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000005 |
| ETIM 3.0 | EC000005 |
| ETIM 4.0 | EC001052 |
| ETIM 5.0 | EC001052 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 27113201 |
| UNSPSC 7.0901 | 27121703 |
| UNSPSC 11     | 27121703 |
| UNSPSC 12.01  | 27121703 |
| UNSPSC 13.2   | 27121703 |

### Drawings

## Cable lug - C-PCI 1,5/2 - 3240064

Dimensioned drawing

