This product is not orderable anymore. Please contact your local distribution partner.



# SEK-18 SV MA STD ANGWW RKZ 60P PLS4



| Image is for | illustration pu | rnoses only | Please refer | to product | description |
|--------------|-----------------|-------------|--------------|------------|-------------|
|              |                 |             |              |            |             |

| Part number        | 09 18 560 5916                         |
|--------------------|--|
| Specification      | SEK-18 SV MA STD ANGWW RKZ 60P<br>PLS4 |
| HARTING eCatalogue | https://b2b.harting.com/09185605916    |

## Identification

| Category                   | Connectors     |
|----------------------------|----------------|
| Series                     | SEK Standard   |
| Element                    | Male connector |
| Description of the contact | Angled         |

### Version

| Termination method | Wrap termination  |
|--------------------|-------------------|
| Connection type    | PCB to cable      |
| Number of contacts | 60                |
| Termination length | 15 mm             |
| Locking type       | With short levers |

## Technical characteristics

| Dimensions wire wrap post          | 0.6 x 0.6 mm       |
|------------------------------------|--------------------|
| Contact rows                       | 2                  |
| Contact spacing (termination side) | 2.54 mm            |
| Rated current                      | 1 A                |
| Insulation resistance              | >10 <sup>9</sup> Ω |
| Contact resistance                 | ≤20 mΩ             |
| Limiting temperature               | -55 +125 °C        |
| Performance level                  | NM 30 (S4)         |
| Mating cycles                      | ≥250               |
| Test voltage U <sub>r.m.s.</sub>   | 1 kV               |

This product is not orderable anymore. Please contact your local distribution partner.



## Technical characteristics

| Isolation group | IIIa (175 ≤ CTI < 400) |  |
|-----------------|------------------------|--|
|-----------------|------------------------|--|

# Material properties

| Material (insert)                         | Thermoplastic resin (PBT)                                   |
|---|---|
| Colour (insert)                           | Grey  |
| Material (contacts)                       | Copper alloy  |
| Surface (contacts)                        | Noble metal over Ni Mating side Sn over Ni Termination side |
| Layer thickness                           | ≥0.76 µm  |
| Layer thickness                           | ≥30 µinch   |
| Material flammability class acc. to UL 94 | V-0   |
| RoHS                                      | compliant   |
| ELV status                                | compliant   |
| China RoHS                                | е   |
| REACH Annex XVII substances               | Not contained   |
| REACH ANNEX XIV substances                | Not contained   |
| REACH SVHC substances                     | Not contained   |
| California Proposition 65 substances      | Yes   |
| California Proposition 65 substances      | Antimony trioxide Lead Nickel                               |
| Requirement set with Hazard Levels        | R26   |

# Specifications and approvals

| Specifications         | IEC 60603-13   |
|------------------------|--|
| UL / CSA               | UL 1977 ECBT2.E102079<br>CSA-C22.2 No. 182.3 ECBT8.E102079 |
| Railway classification | F3/I3  |

## Commercial data

| Packaging size                 | 50            |
|--------------------------------|---------------|
| Net weight                     | 24 g          |
| Country of origin              | Switzerland   |
| European customs tariff number | 85366990      |
| GTIN                           | 5713140034846 |

Product data sheet 09 18 560 5916 SEK-18 SV MA STD ANGWW RKZ 60P PLS4

This product is not orderable anymore. Please contact your local distribution partner.



### Commercial data

eCl@ss

27460201 PCB connector (board connector)

### Cross section of solder termination

