

B45396R, Tantalum, MnO2 Tantalum, Multi-Anode, 150 uF, 10%, 16 V, SMD, Molded, Ultra Low ESR, 40 mOhms, 7343, Height Max = 4.4mm



| General Information | |
|---------------------|--|
| Supplier: | KEMET |
| Series: | B45396R |
| Dielectric: | MnO2 Tantalum |
| Style: | SMD Chip |
| Description: | SMD, Molded, Ultra Low ESR |
| Features: | Ultra Low ESR |
| RoHS: | Yes |
| Termination: | Tin |
| Miscellaneous: | Closest Kemet Original Series Equivalent: T510X157K016AT |
| Notes: | Obsolete. Old Part Number [Obsolete] Was B45396R3157K509 |

| Dimensions | |
|------------|----------------|
| Footprint | 7343 |
| L | 7.3mm +/-0.3mm |
| W | 4.3mm +/-0.3mm |
| H | 4.1mm +/-0.3mm |
| S | 1.3mm +/-0.3mm |
| F | 2.4mm +/-0.1mm |
| K | 1.8mm TYP |

| Packaging Specifications | |
|--------------------------|------------|
| Packaging: | T&R, 178mm |
| Packaging Quantity: | 400 |

| Specifications | |
|------------------------|---|
| Capacitance: | 150 uF |
| Capacitance Tolerance: | 10% |
| Voltage DC: | 16 VDC (85C), 10.72 VDC (125C) |
| Temperature Range: | -55/+125C |
| Rated Temperature: | 85C |
| Dissipation Factor: | 6% |
| Failure Rate: | N/A |
| Resistance: | 0.04 Ohms (100kHz) |
| Current: | 2600 mAmps (25C), 2340 mAmps (85C), 1040 mAmps (125C) |
| Leakage Current: | 24 uA |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.